

[1] LOCATION OF WATER WELL: County: Reno		Fraction NW ¼ SW ¼ SE ¼	Section Number 12	Township Number T 2 S	Range Number R 5 E/W
Distance and direction from nearest town or city street address of well if located within city? 298' E & 520' N of Lorraine & Carey Blvd Hutchinson KS					
[2] WATER WELL OWNER: Kansas Dept. of Health & Environment - DEK					
RR#, St. Address, Box # : Furber Field, Bldg 740			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Topeka Kansas 66620-0001			Application Number:		
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		[4] DEPTH OF COMPLETED WELL: 43' ft. ELEVATION: 1527.04			
A diagram showing a section box divided into four quadrants (NW, NE, SW, SE). An 'X' marks the location of the water well in the NW quadrant.		Depth(s) Groundwater Encountered 1 28.64 ft. 2 . ft. 3 . ft.			
		WELL'S STATIC WATER LEVEL 28.64 ft. below land surface measured on mo/day/yr 10/10/96			
		Pump test data: Well water was . ft. after . hours pumping gpm			
		Est. Yield . gpm: Well water was . ft. after . hours pumping gpm			
		Bore Hole Diameter . 8.4 in. to 43 ft., and . in. to . ft.			
WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only @ Monitoring well MP-SM					
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No					
[5] TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped @ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter . 2 in. to 38 ft. Dia . in. to . ft. Dia . in. to . ft. Casing height above land surface . 24 in. weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: @ PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot @ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 43 ft. to 38 ft. From . ft. to . ft. GRAVEL PACK INTERVALS: From 43 ft. to 36 ft. From . ft. to . ft.					
[6] GROUT MATERIAL: @ Neat cement 2 Cement grout @ Bentonite 4 Other Grout Intervals: From 36 ft. to 21 ft. From 21 ft. to 8 ft. From . ft. to . ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy @ Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)					
Direction from well? Northeast How many feet? 430'E & 360'N					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	10	Bkn Clay			
10	43	Yel Brn Sand & Gravel			
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-10-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 568 This Water Well Record was completed on (mo/day/yr) 10-10-96 under the business name of MARS by (signature) David Swathen					