

LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 35 Township Number T 23 S Range Number R 5 EW

Distance and direction from nearest town or city street address of well if located within city?

3 East 2 South of Big "M" Truck Stop on Hwy 50, Hutchinson, KS.

WATER WELL OWNER: KAW DRIS Co INC

IR#, St. Address, Box #: 1010 UNION CENTER BLDG

City, State, ZIP Code: Wichita, KS 67202

Board of Agriculture, Division of Water Resources

Application Number: T-85-420

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION: 1498 GL

Depth(s) Groundwater Encountered 1. 13 ft. 2. 13 ft. 3. 13 ft.

WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 4/24/85

Pump test data: Well water was 13 ft. after 4 hours pumping 13 gpm

Est. Yield 13 gpm: Well water was 13 ft. after 4 hours pumping 13 gpm

Bore Hole Diameter 13 in. to 13 ft., and 13 in. to 13 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil well water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter 5 1/2 in. to 5 1/2 ft., Dia 5 1/2 in. to 5 1/2 ft., Dia 5 1/2 in. to 5 1/2 ft.

Casing height above land surface 3 ft. Below weight 13 lbs./ft. Wall thickness or gauge No. 13

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 55 ft. to 3 ft., From 55 ft. to 3 ft.

From 55 ft. to 3 ft., From 55 ft. to 3 ft.

GRAVEL PACK INTERVALS: From 55 ft. to 3 ft., From 55 ft. to 3 ft.

From 55 ft. to 3 ft., From 55 ft. to 3 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 55 ft. to 3 ft., From 55 ft. to 3 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? Northwest How many feet? 100

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

55 3 Circulated 15 SKS CEMENT WITH 3 HALLIBURTON PUMP TRUCK

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

completed on (mo/day/year) 5/2/85 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 5/2/85 This Water Well Record was completed on (mo/day/yr) 5/4/85

Under the business name of KAW DRIS Co INC by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top

three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL

OWNER and retain one for your records.