

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		SE ¼ NW ¼ NW ¼	19	T 23 S	R 5 E
Distance and direction from nearest town or city street address of well if located within city? 609 E. Avenue G, Hutchinson					
2 WATER WELL OWNER: Cargill Salt					
RR#, St. Address, Box # : PO Box 1403			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Hutchinson, Kansas 67504			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 1526.66			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 17.91 ft. below land surface measured on mo/day/yr 4/20/2006 Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 25 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No ✓ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ✓			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
Blank casing diameter 2 in. to 15 ft. Dia. in. to ft. Dia. in. to ft.		7 Fiberglass		Threaded. ✓	
Casing height above land surface -5.28 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40		TYPE OF SCREEN OR PERFORATION MATERIAL			
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement		8 RMP (SR) 11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 13 ft. to 25 ft. From ft. to ft.		FROM ft. to ft. FROM ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete					
Grout Intervals: From 0 ft. to 2 ft. From 2 ft. to 13 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		Former UST			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		How many feet?			
Direction from well?					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 1 Asphalt,					
1 4.5 Sand, v. clayey, occ. gravel, prob. fill, Brown					
4.5 8 Sand (vf), v. silty, moist, no odor, Brown					
8 18 Sand (f-c w/f gravel), dry, no odor, Lt. Brown					
18 25 Sand (f-c w/tr. f gravel), silty, moist-sat. @ 20',					
MW1/SB1, Tag # 00371207, Flushmount					
Project Name: Cargill Salt					
GeoCore # 1259, KDHE # U2 078 13664					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/17/2006 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 5/19/06					
under the business name of GeoCore, Inc. by (signature) Dale Bell					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					