


1 LOCATION OF WATER WELL: Fraction NW ¼ NE ¼ NW ¼ Section Number 21 Township Number T 23 S Range Number R 5 E/W
County: Reno

Distance and direction from nearest town or city street address of well if located within city?
Avenue G and Commerce, Hutchinson, Kansas.

2 WATER WELL OWNER: City of Hutchinson
RR#, St. Address, Box # : P.O.Box 1567
City, State, ZIP Code : Hutchinson, Kansas 67504
Board of Agriculture, Division of Water Resources
Application Number: 20059051

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL 57 ft. ELEVATION: 93-27-06
 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 9 ft. below land surface measured on mo/day/yr 03-27-06
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Contamination
 Remediation
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded X
 Blank casing diameter 16 in. to 37 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 24 in., weight SCH 80 lbs./ft. Wall thickness or gauge No. .9062
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 57 ft. to 37 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 37 ft. to 32 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Hole Plug
 Grout Intervals: From 32 ft. to 24 ft., From 24 ft. to 4 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? SE How many feet? 1,000 4th & Carey contamination remediation

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	9	Brown Clay			
9	13	Brown Clay and Small Sand Mix			
13	23	Small Sand and Gravel			
23	27	Large to Medium Gravel			
27	40	Medium to Small Gravel			
40	50	Medium to Small Gravel			
50	54	Small Gravel			
54	56	Small to Medium Gravel			
56	57	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03-27-06 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's Licence No 134 This Water Well Record was completed on (mo/day/yr) 04-28-06
 under the business name of Rosencrantz-Bemis Ent. by (signature) *Jesse Dodson*