

WATER WELL RECORD Form WWC-5 KSA 82a-1212

[1] LOCATION OF WATER WELL:		Fraction	Township Number	Range Number
County: Reno	SE ¼ NE ¼ SE ¼	5	T 23 S	R 5 E/W
Distance and direction from nearest town or city street address of well if located within city? 1700 N. Halstead Road, Hutchinson				
[2] WATER WELL OWNER: ADM				
RR#, St. Address, Box # : 4666 Faries Parkway	Board of Agriculture, Division of Water Resources Application Number:			
City, State, ZIP Code : Decatur, IL 62521				
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	[4] DEPTH OF COMPLETED WELL 25 ft. ELEVATION:			
N W NW NE E SW SE X S	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr 4/3/2006 Pump test date: Well water was NA ft. after hours pumping gpm Est. Yield NA gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 27 ft., and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No✓ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ✓			
[5] TYPE OF BLANK CASING USED:				
1 Steel		3 RMP (SR)		CASING JOINTS: Glued Clamped Welded Threaded ✓
(2) PVC		4 ABS		
Blank casing diameter 2 in. to 15 ft., Dia. lbs./ft. Wall thickness or gauge No. Sch. 40.				
Casing height above land surface 0 in., weight				
TYPE OF SCREEN OR PERFORATION MATERIAL				
1 Steel		3 Stainless steel		(7) PVC
2 Brass		4 Galvanized steel		10 Asbestos-cement
		6 Concrete tile		11 Other (specify)
				12 None used (open hole)
SCREEN-OR PERFORATION OPENINGS ARE:				
1 Continuous slot		(3) Mill slot		8 Saw cut
2 Louvered shutter		4 Key punched		9 Drilled holes
				10 Other (specify)
SCREEN-PERFORATED INTERVALS:				
From 15 ft. to 25 ft.		From ft. to ft.		
GRAVEL PACK INTERVALS:				
From 13 ft. to 25 ft.		From 25 ft. to 27 ft.		
[6] GROUT MATERIAL:				
1 Neat cement		2 Cement grout		(3) Bentonite
				(4) Other Concrete
Grout intervals: From 0 ft. to 1 ft. From 1 ft. to 15 ft. From ft. to ft.				
What is the nearest source of possible contamination?				
1 Septic tank		4 Lateral lines		7 Pit privy
2 Sewer lines		5 Cess pool		8 Sewage lagoon
3 Watertight sewer lines		6 Seepage pit		9 Feedyard
				10 Livestock pens
				11 Fuel storage
				12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
Direction from well? How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	PLUGGING INTERVALS
0	1	Topsoil, organic, rich, sandy, silty,		
1	4	Silt, tr. sand, moist, Dark Brown		
4	10	Sand, silty, moist, Orange		
10	15	Sand (to vc), moist to v. moist, Pink		
15	27	Sand and gravel (m-vc), multicolored washed s		
				MW4 , Flushmount
				Project Name: Huff Huff - ADM Hutch
				GeoCore # 1285 , #
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 5/31/2006 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 527	This Water Well Record was completed on (mo/day/yr) 5/31/2006			
under the business name of GeoCore, Inc.		by (signature) [Signature]		
INSTRUCTIONS : Use typewriter or ball point pen. PLEASE PRESS FIRMLY AND PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.				