

1 LOCATION OF WATER WELL:

County: Reno

Distance and direction from nearest town or city street address of well if located within city?
36 Lawndale PK Hutch KS

Fraction SW 1/4 NE 1/4 SE 1/4

Section Number 6

Township Number T 23 S

Range Number R 5 EW

2 WATER WELL OWNER:

RR#, St. Address, Box # 36 Lawndale PK

City, State, ZIP Code Hutchinson, KS 67502

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N

--NW--

--NE--

--SW--

--SE--

W

E

S

4 DEPTH OF COMPLETED WELL

ft. 32

Depth(s) Groundwater Encountered (1) 14 ft. (2) 14.5 ft. (3) 28-22-0 ft.

WELL'S STATIC WATER LEVEL 14.5 ft. below land surface measured on mo/day/yr PK

Pump test data: Well water was 14.5 ft. after PK hours pumping 25 gpm

Est. Yield 25 gpm: Well water was 14.5 ft. after PK hours pumping 25 gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr

Sample was submitted PK Water well disinfected? Yes X No PK

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)

2 PVC 4 ABS 5' 7 Fiberglass

Blank casing diameter 5 in. to 22 ft., Diameter 22 in. to 22.9 ft., Diameter 180 in. to PK ft.

Casing height above land surface 12 in., Weight 22.9 lbs./ft. Wall thickness or gauge No. 180

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)

2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 22 ft. to 32 ft., From PK ft. to PK ft.

GRAVEL PACK INTERVALS: From 14 ft. to 32 ft., From PK ft. to PK ft.

6 GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 1 ft. to 19 ft., From PK ft. to PK ft., From PK ft. to PK ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify)

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well

Direction from well? E How many feet? 25

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 10 Fine dirt 0 10

10 14 Sand 10 14

14 32 Peasize gravel 14 32

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:

This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-22-01 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 255 This Water Well Record was completed on (mo/day/year) 8-22-01

under the business name of Wilson Water Systems by (signature) E. Wilson

INSTRUCTIONS:

Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdhe.state.ks.us/geo/waterwells>.