1 LOCATIO	ON OF WATE	R WELL:	Fraction	· · · · · · · · · · · · · · · · · · ·		Section	Numb	er Townshin	Number	Rang	e Numbe	er
County:		eno	SE 1/4	SW 1/4	SE 1/		14		S	R	_	W
			n or city street add				· · ·					
4 th and A	irport Rd.,	Hutchinson	n									
			s Departmen		nd Envi	ronmen	t					
			W Jackson,	Ste. 410				Board of Ag	riculture, Div	ision of Wa	ter Reso	urces
City, State, 2	ZIP Code	: Topeka	a, KS 66612					Application	Number:			
3 LOCATE	WELL'S LOC	CATON WITH	4 DEPTH OF C	OMPLETED WE	1.1	95	ft FI	EVATION:	1503	3.73 (TO	C)	
	i SECTION B	<u> </u>	Denth(s) Ground	vater Encountere	d 1	8	- 11. LL	# 2	ft	3	٠,	
			Depth(s) Grounds WELL'S STATIC	MATED I EVE	u '	ft ho	low lan	d surface measure	d on molday	her		11.
	NW	- NE	Pump	test data: Wel	l water was	11. De	iuw iai i	f offer	boure	numnina		
		E	Est. Yield	apm: Wel	l water was	·		ft. after	hours	pumping ₋		gpm gpm
			Poro Holo Diame	gpiii. Wei	n to	95		ft and	i	pumping ₋		gpiii
	sw	- SE	Bore Hole Diame WELL WATER TO 1 Domestic	D BE USED AS:	5 Public	water supp	oly	8 Air condi	tioning 1	1 Injection	well	
		x	1 Domestic	3 Feed lot	6 Oil fiel	d water su	pply	9 Dewater	ing 1	2 Other (S	pecify be	elow)
, ∟		X!	2 Irrigation	4 Industrial	7 Lawn	and garder	(dome	stic) 10 Monitor	ring well			
	S		Was a chemical/b					nt? Yes No				
			submitted				١	Water Well Disinfe	cted? Yes		No X	
5 TYPE OF	F BLANK CAS	SING USED:		5 Wrought Iro	on 8	Concrete	tile	CASING J	OINTS: Glue	ed	Clamped	d
1 Ste	el	3 RMP (SR)						Wel			
2 PV	С	4 ABS		7 Fiberglass		•			Threa	ded	Flusi	n
			in. to 85									
Casing heig	ht above land	surface F	lushmount	n weight	0.70)3	lbs./	/ft. Wall thickness	or gauge No	S	CH. 40)
			N MATERIAL:	,		7 P	VC	10 A	sbestos-cem	ent		
1 Ste	el	3 Stainle	ess steel	5 Fiberglass		8 RI	MP (SR	8) 11 0	ther (specify))		
2 Bra	ISS	4 Galvar	nized steel	6 Concrete til	le	9 AI	BS	12 N	one used (op	en hole)		
		TION OPENIN						8 Saw cut		11 None	(open h	ole)
	ntinuous slot		Mill slot	6	Wire wrap	ped		9 Drilled ho				
2 Lou	vered shutter	4	Key punched		Torch cut			10 Other (sp	ecify)			
SCREEN-P	ERFORATED	INTERVALS:						t. From				
			From	ft. to			ft	t. From	ft.	to		ft.
		NTERVALS:						t. From				
			From	ft. to			ft	t. From	ft.	to		ft.
6 GROUT	MATERIAL:	1 Neat o	From 2	Cement grout		3 Bento	nite	4 Other				
Grout Interv	als From	1	ft. to 82	ft. From		ft. to		ft. Fron	n	ft. to		ft.
What is the	nearest source	e of possible of	contamination:					vestock pens				J.
	ptic tank		4 Lateral lines					iel storage				
			5 Cess pool			on			16 O	ther (specify	/ below)	
	tertight sewer	lines	6 Seepage pit	9 F	eedyard			secticide storage				
Direction fro	m well?	CODE	LITHOL	OGIC LOG		FROM	How ma	any feet?	PLUGGING I	NTED\/ALS		
FROW	10		ay, dark brown			FROW	10		r LOGGING I	IVILIVALO	·	
0	15		sandy below 8		,							
		Sa	nd, light brown	to medium br								
4=	0.5		y fine to very co	arse grained, v	with							
15	95	gra	ivel below 25'									

7 CONTRA	ACTOR'S OR	LANDOWNE	R'S CERTIFICATI		well was (1)) constructe	d, (2) r	econstructed, or (3) plugged und	der my jurisc	liction ar	id was
	on (mo/day/yr		06/0					is true to the best				
Water Well	Contractor's I	icense No.		531				l Record was com	pleter on (mo	o/day/yr)	06/19	3/08
under the b	usiness name	of	Geotechnic	al Services	Inc.	by (:	signatui	re) //y/L	14			
INSTR	UCTIONS:. PI	ease fill in blank	s and circle the corr	ect answers. Sen	d three copie	es to Kansas	Depart	ment of Mealth and I	Envirønment, E	Bureau of Wa	ter, 1000	SW