WATER WELL RE	CORD	Form W	WC-5	Di	vision of Wate	r Resources App. N	0.	
1 LOCATION OF WATER WELL:		Fraction ¹ / ₄ NW ¹ / ₄ NE	1/4 NW 1/4	Section	on Number 6	Township No. T 23 S	Range Number R 5 □E ☑W	
		f unknown, distance &	Globa	Global Positioning System (GPS) information:				
from nearest town or i		Latitude: .N38,086 (in decimal degrees) Longitude: W97,91672 (in decimal degrees)						
7303 East 30th Avenue, Hutchinson, Kansas				Elevation: Unknown Datum: WGS 84, M NAD 83, NAD 27				
2 WATER WELL OWNER: MRP Properties, Inc.					Collection Method:			
RR#, Street Address, Box #: 5590 Havana Street				GPS unit (Make/Model: Garmin Nuvi 760				
City, State, ZIP Code		CO 50938		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
3 LOCATE WELL	A DEPTH OF	COMPLETED WELL	20 15					
WITH AN "X" IN SECTION BOX: N 4 DEPTH OF COMPLETED WELL 29.15 ft. (2).NA ft. (3).NA ft. (3).NA ft. (2).NA ft. (3).NA ft. (3).NA ft. (4).NA ft. (5).NA ft. (6).NA ft. (7).NA ft. (8).NA ft. (8).NA ft. (8).NA ft. (8).NA ft. (9).NA ft. (1).NA ft								
Pump test data: Well water was NA								
EST. YIELD. NAgpm. Well water was. NAft. after. NA hours pumping. NAgp								
W E Bore Hole Diameter 8.49in. to .49.19ft., and .NAin. to .NAft.								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Oil field water supply Dewatering Other (Specify below								
SW - SE - Irrigation Industrial Domestic-lawn & garden								
S If yes, mo/day/yr sample was submitted.NA								
1 mile Water well disinfected?								
5 TYPE OF CASING CASING IOINTS:	Glued	nned D Welded	7 Threaded	1				
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .4								
Casing height above land surface. 0. in., Weight NA. lbs./ft., Wall thickness or gauge No. Schedule 40.								
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ✔ PVC ☐ Other (Specify)								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)								
SCREEN-PERFORATE	ED INTERVALS:	From 9.15	it. to29.15 it. toNA	5	ft., From ft., From	NA ft. NA ft.	toNA ft. toNA ft.	
GRAVEL PACK INTERVALS: From Unknown ft. to Unknown ft., From NA ft. to NA ft. From NA ft. to NA ft., From NA ft. to NA ft. 6 GROUT MATERIAL: Neat cement Cement Grout Bentonite Other								
Grout Intervals: From What is the nearest source	1 .0 ft. to		NA Benton	ft. to	Other IA ft.,	From .NA	ft. to .NAft.	
Septic tank								
☐ Watertight sewer	lines Seepage p	it Feedyard	Fertilizer s	torage	Oil well/ga	as well		
Direction from well					ell<1.00'			
FROM TO	LITHOLOG	IC LOG	FROM	TO			GGING INTERVALS	
			-	8" 29.15	Bentonite	nd Grass Seed		
			0	29.15		overdrilled		
					:			
7 CONTRACTOR'S O	R LANDOWNER	'S CERTIFICATION	N: This water	er well v	vas 🗌 constr	ucted, \square reconstr	ucted, or 🗹 plugged	
under my jurisdiction an Kansas Water Well Cont	ractor's License N	o. 759 This V	Vater Well R	ecord w	as completed	lon (mo/day/year)		
under the business name							20 7	
INSTRUCTIONS: Use types (white, blue, pink) to Kansas Telephone 785-296-5522. See	Department of Health	and Environment, Bureau	of Water, Geole	ogy Section	on, 1000 SW Ja	ckson St., Suite 420,	Topeka, Kansas 66612-1367.	
http://www.kdheks.gov/waterv								
KSA 82a-1212				Cł	neck: 💢 Wl	hite Copy, 🔲 Bl	ue Copy, 🔲 Pink Copy	