HON-4D Division of Water Resources App. No. Form WWC-5 WATER WELL RECORD Range Number Township No. Section Number 1 LOCATION OF WATER WELL: Fraction 24 23 S R 5 1/4 SW 1/4 SW 1/4 NW 1/4 County: Reno Global Positioning System (GPS) information: Street/Rural Address of Well Location; if unknown, distance & direction Latitude: .38.0597..... (in decimal degrees) from nearest town or intersection: If at owner's address, check here . well is located east side of S. Mayfield Rd. approx. Longitude: 97.8670 (in decimal degrees) Elevation: 1520 2000 ft south of Avenue & in Hutchinson, KS Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27 WATER WELL OWNER: Honeywell International, Inc. Collection Method: ☐ GPS unit (Make/Model: Garmin 60C) RR#, Street Address, Box #: 111 S.34th St. M/S 158 City, State, ZIP Code Phoenix, AZ 85034 3 LOCATE WELL 4 DEPTH OF COMPLETED WELL 67 ft. WITH AN "X" IN Depth(s) Groundwater Encountered (1).10. ft. (2).-.... ft. (3)..... ft. SECTION BOX: WELL'S STATIC WATER LEVEL 10ft. below land surface measured on mo/day/yr..10/06/11...... N EST. YIELD......gpm. Well water was.......ft. after....... hours pumping.......gpm -- NE --- NW - -Bore Hole Diameter 8......in. to .67......ft., andin. toft. ☐ Geothermal ☐ Injection well WELL WATER TO BE USED AS: Public water supply ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Domestic-lawn & garden ☐ Monitoring well ☐ Feedlot □ Domestic - - SW - --- SE --☐ Industrial ☐ Irrigation If yes, mo/day/yr sample was submitted..... S |-----1 mile------| Water well disinfected? \(\subseteq \text{ Yes } \subseteq \text{ No Other V PVC 5 TYPE OF CASING USED: ☐ Steel CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .2...... in. to .57...... ft., Diameter .7...... in. to .7..... ft., Diameter .7..... ft., Diameter .7..... ft. TYPE OF SCREEN OR PERFORATION MATERIAL: Other (Specify) ☐ Stainless Steel ✓ PVC☐ None used (open hole) ☐ Steel Galvanized Steel Brass SCREEN OR PERFORATION OPENINGS ARE: None (open hole) Other (specify) SCREEN-PERFORATED INTERVALS: From ... 67 ft. to ... 57 ft., From ... ft., From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 67 ft. to .53 ft., From .7 ft. to ..7 ft. to ..7 6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other.... From .53 ______ ft. to .2 _____ ft., From ... ____ ft. to ... ____ ft., From ... ___ ft., From ... ___ ft. What is the nearest source of possible contamination: ☐ Livestock pens ☐ Insecticide storage ☐ Abandoned water well ☐ Fertilizer storage ☐ Oil well/gas well Other (specify below) ☐ Septic tank
☐ Sewer lines ☐ Lateral lines ☐ Pit privy Cesspool Sewage lagoon Fuel storage ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard Distance from well Direction from well LITHO. LOG (cont.) or PLUGGING INTERVALS FROM TO LITHOLOGIC LOG FROM TO Silt w/fine sand 0 67 7 Sand, poorly sorted 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was

✓ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) .10/04/2011 and this record is true to the best of my knowledge and belief. INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.

KSA 82a-1212

Check: White Copy, Blue Copy, Pink Copy