WATER WELL REC	ORD	Form W	WC-5	Division of Water	r Resources App. No	
1 LOCATION OF WAT	ER WELL:	Fraction	- \	Section Number	Township No. T 23 S	Range Number R 5 □E 🗷W
Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning	System (GPS) in	formation:
from nearest town or int	Latitude: 50.0.2	2 de salv.	(in decimal degrees)			
from nearest town or intersection: If at owner's address, check here				Global Positioning System (GPS) information: Latitude: 38.03.25.10		
2700 E. 4th Aue; Hutchinson, Ks.				Datum: WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: Willon Real Estate				Collection Method:		
RR#, Street Address, Box #:			GPS unit (Make/Model:)			
City, State, ZIP Code : A 100 G. 4. Hite Witch William, Ks. 67501			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL		•			<u> </u>	hand 1
WITH AN "X" IN	4 DEPTH OF C	COMPLETED WELL	L	ft.	2	2)
SECTION BOX: Depth(s) Groundwater Encountered (1)5						
	Pump	test data: Well wate	r was	ft. after	hours pum	ping gpm
] 1111 112	EST. YIELD	gpm. Well wate	r was	ft. after	hours pum	ping gpm
		eter 1/9 in. to TO BE USED AS:				
	□ Domestic					Other (Specify below)
		☐ Industrial ☐				
Was a chemical/bacteriological sample submitted to Department? Yes X No						
S If yes, mo/day/yr sample was submitted						
water win districted: 1 Tes A 100						
5 TYPE OF CASING USED: Steel YVC Other Other						
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 3.3.15 in. to						
Casing height above land surface. Flush, Mt. in., Weight						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
Steel Stainless Steel PVC Other (Specify)						
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot						
□ Louvered shutter □ Key punched □ Wire wrapped □ Saw cut □ Other (specify)						
SUKEEN-PERFURATED INTERVALS: From						
From						
Evan ft to ft From . ft to ft						
6 GROUT MATERIAL: Neat cement , Cement grout Bentonite Other Condition						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Compatible. Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft. From ft. to ft.						
What is the nearest source of possible contamination: Septic tank						
Sewer lines						
Watertight sewer lin		oit Feedyard	Fertilizer st	-		
Direction from well				from well		
FROM TO GLACE	LITHOLOG	IIC LUU	FROM	TO LITHO. LO	OO (cont.) or PLC	JGGING INTERVAL
0 6.0 8000	ilfu tank	Di Q				
6.0 10.5 Tan U	autual	E ,	*			
10.5 15,0 BUN V	eutine a	naired-to-fi	egaine	262		
15 p 20 p 0 . 5 0	sol	inel pandy	20 446 4 1			
15.0 20.0 Bun C	BUSI. GUL	INDIV DIVINOV	HULLER			
		MM (1974) - 1774			Power	January
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🔀 constructed, 🗆 reconstructed, or 🔲 plugged						
under my jurisdiction and was completed on (mo/day/year) . All						
under the business name of 38 cavus myent 22 Drilling. by (signature) Campo Bioker						
INSTRUCTIONS: Use typewriter of ball point pen. PLEASE PRESS FIRMLY and PRINT elearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
(white, blue, pink) to Kansas Do	epartment of Health	and Environment, Bureau	of Water, Geolo	ogy Section, 1000 SW Ja your records Include fe	eckson St., Suite 420, e of \$5.00 for each of	Topeka, Kansas 66612-136 constructed well. Visit us
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212						