mw - 31 d WATER WELL RECORD

/NW - 3						
	LL RECORD	Form V	VWC-5		Water Resources App. N	
,	NOF WATER WELL:	Fraction		Section Numb	er Township No.	
County: Re		NW 1/4 NW 1/4 SI			T 23 S	
	Address of Well Location;		Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here				Latitude: 1.80.34.4.3.14		
1/2 mi. west of Obee Road and US Hwy 50 on north side of Hwy 50				Elevation: (in decimal degrees)		
				Datum: WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: VIGindustries				Collection Method:		
RR#, Street Address, Box #: 3033 Campus Drive				GPS unit (Make/Model:)		
City, State, ZIP Code : Plymouth, MN 55441				☐ Digital Map/Photo, ☐ Topographic Map, ☒ Land Survey		
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m						
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 76.0 ft.						
SECTION BOX: Depth(s) Groundwater Encountered (1)						
SECTION BOX: Depth(s) Groundwater Encountered (1)						
Pump test data: Well water was the after hours numping grow						
NW NE EST. YIELD						
W X NW - E Bore Hole Diameter 3.25 in. to 83.0 ft., and in. to ft.						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
sw	D-mastic	☐ Feedlot ☐	Oil field water	r supply	Dewatering	Other (Specify below)
	│					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No						
S If yes, mo/day/yr sample was submitted						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded						
Casing diameter .1 in. to						
Casing height above land surface. 0 in., Weight						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From71.0						
		From	. ft. to	ft., Fron	n ft.	to ft.
GRAV	EL PACK INTERVALS:					
From						
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other						
Grout Intervals: From .0						
What is the nearest source of possible contamination: Septic tank						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
	ght sewer lines 🔲 Seepage p	it 🗌 Feedyard	Fertilizer sto	orage 🔲 Oil we	ll/gas well	
Direction fro	m well		Distance f	rom well		
FROM TO	LITHOLOG	IC LOG	FROM	TO LITHO	. LOG (cont.) or PLU	JGGING INTERVALS
0 11.0	sand with silt and clay					
11.0 76.0	sand					
76.0 80.0	sand and shale					
80.0 83.0	shale					
					·	
			 -			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year)						
under my jurisd	iction and was completed or	1 (mo/day/year) .!	1.1.7.59.1.	unis record is tr	ue to the best of my k	nowledge and belief.
Nansas Water V	Vell Contractor's License Ness name ofEnvironment	al Priority Service	water well Re	by (signature)	tion on (mo/day/year)	:
	Use ty pewriter or ball point pen.					
(white, blue, pink)	to Kansas Depar tment of Health	and E nvironment, Bureau	of Water, Geolog	y Section, 1000 SV	Jackson St., Suite 420,	Topeka, Kansas 666 12-1367.
	-5524. Send one copy to WAT	ER WELL OWNER and	retain one for yo	our records. Include	e fee of \$5.00 for each co	nstructed well. Vi sit us at
http://www.kdheks.j KSA 82a-1212	gov/waterwell/index.html.		,	Check:	White Copy, Bl	ue Copy, Pink Copy
3U/3 U40"1414				CHOOK.	Cob2, DI	~ COPJ, LILIK COPJ