## MW - 30 d

WATER WELL R	FCODD	Form W	WC.5	Division of Wate	n Docouroos Ann M	
1 LOCATION OF W		Form W	WC-3	Section Number	r Resources App. No	
County: Reno		SW 1/4 SW 1/4 SV	V 1/4 SE 1/4		T 23 S	
Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:		
from nearest town or intersection: If at owner's address, check here .				Latitude:		
1/2 mi. west of Obee Road and US Hwy 50 on north side of Hwy 50				Longitude:1.1.1.1.7.3.8.7.1.2.7 (in decimal degrees)		
				Elevation:		
2 WATER WELL OWNER: Vigindustries				Datum: WGS 84, NAD 83, NAD 27 Collection Method:		
RR#, Street Address, Box #: 3033 Campus Drive				GPS unit (Make/Model:)		
City, State, ZIP Code : Plymouth, MN 55441				🔲 Digital Map/Photo, 🗋 Topographic Map, 🛛 Land Survey		
				Est. Accuracy: <a>[ &lt;3 m, ]</a> 3-5 m, <a>[ 5-15 m, ]</a> >15 m		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 48.0						
WITH AN "X" IN SECTION BOX:4 DEPTH OF COMPLETED WELL .45.9 Depth(s) Groundwater Encountered (1)						
N WELL'S STATIC WATER LEVEL. 10.42						
Pump test data: Well water wasft. after hours pumping						
EST. YIELD						
$  _W   _I   _E$ Bore Hole Diameter 3.25						
│ ┝─┼─┼─┽─┥	WELL WATER	TO BE USED AS: [	Public wate	er supply 🛛 🔲 Ge	othermal 🗌 L	njection well
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
Irrigation   Industrial   Domestic-lawn & garden M Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes V No						
S If yes, mo/day/yr sample was submitted Water well disinfected? Yes Y No						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Glued Clamped Welded I Threaded Casing diameter .1 in. to .38.0 ft., Diameter in. to ft., Diameter in. to ft.						
Casing diameter						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
□ Steel □ Stainless Steel						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
□ Continuous slot						
SCREEN-PERFORATED INTERVALS: From						
		From	ft. to	ft., From	ft. t	to ft.
GRAVEL PA						to ft.
From						
6 GROUT MATERIAL:  Neat cement Cement grout Bentonite Other						
Grout Intervals: From						
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well						
				from well		
FROM TO	LITHOLOG	IC LOG	FROM	TO LITHO. LO	JG (cont.) <u>or</u> PLU	GGING INTERVALS
	with silt and clay		<u> </u>			·
10.5 48.8 sand 48.8 52.0 shale			+			
48.8 52.0 shale	<u>)</u>		++-			
			++-			
	·····					· · · · · · · · · · · · · · · · · · ·
		<u> </u>				
	·····					
						· · · · · · · · · · · · · · · · · · ·
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🛛 constructed, 🗋 reconstructed, or 🗋 plugged						
under my jurisdiction and was completed on (mo/day/year) /115						
under the business nam						answers. Send three copies
(white, blue, pink) to Kansa	s Depar tment of Health	and E nvironment, Bureau	of Water, Geolo	gy Section, 1000 SW Ja	kson St., Suite 420, 7	Topeka, Kansas 666 12-1367.
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed, well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.						
http://www.kuncks.gov/wate	I WORN HIGGX, HURH.					