MW-305

WATER WELL	RECORD	Form W	WC-5			0	
1 LOCATION OF	WATER WELL:	Fraction		Section Number			
County: Reno		SW 1/4 SW 1/4 SW	1/4 SE 1/4	22	T 23 S	R 5 □E ☑W	
	ress of Well Location;		Global Positioning System (GPS) information:				
	n or intersection: If at		Latitude: 18.5.9.0.328 (in decimal degrees) Longitude: 14.5.7.38 (in decimal degrees)				
1/2 mi. west of Obee Road and US Hwy 50 on north side of Hwy 50				Longitude:1.4.1			
				Elevation:1.50.53.9			
2 WATER WELL OWNER: Vigindustries				Datum: WGS 84, NAD 83, NAD 27			
Vigiriodotiloo				Collection Method: GPS unit (Make/Model:)			
C'i Ci				☐ Digital Map/Photo, ☐ Topographic Map, ☒ Land Survey			
City, State, Zir	Plymout	h, MN 55441		Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m			
3 LOCATE WELL							
1	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 20.0 ft.						
SECTION BOX:	X: Depth(s) Groundwater Encountered (1)						
N	WELL'S STATIC WATER LEVEL10.51ft. below land surface measured on mo/day/yr						
	Pump test data: Well water wasft. after hours pumpinggpm						
NW NE	NE EST. YIELDgpm. Well water wasft. after hours pumping gpm						
w	E Bore Hole Diameter A.49						
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes Yo							
S If yes, mo/day/yr sample was submitted							
Water well disinfected? ☐ Yes ☑ No							
5 TYPE OF CASING USED: Steel V PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .1 in. to .10.0 ft., Diameter in. to ft., Diameter ft.							
Casing height above land surface. 0							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
Steel Stainless Steel PVC Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Continuous slot Mill slot Gauze wrapped Forch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From 10.0 ft. to 20.0 ft., From ft. to ft.							
From							
GRAVEL PACK INTERVALS: From 8.0 ft. to .20.0 ft., From ft. to ft.							
From							
6 CROUT MATERIAL: Next cement Cement grout 7 Rentonite Other							
Grout Intervals: From . ft. to . 8.0 ft., From . ft. to ft., From . ft. to ft.							
What is the nearest source of possible contamination:							
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well							
	ell			rom well		CODIC PUTTO	
FROM TO	LITHOLOG	IC LOG	FROM	TO LITHO, LO	or PLU	GGING INTERVALS	
10.0	nd with silt and clay						
10.5 20.0 sai	nd						
		1					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .11.7.5.7.2.1.7 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 604 This Water Well Record was completed on (mo/day/year)							
under the business name of Environmental Priority Service, Inc. by (signature)							
INSTRUCTIONS: Use ty pewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar truent of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.							
						opeka, Kansas ooo 12-130 /. istructed_well. Vi sit us at	
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							