(m)	N-3	51						
WATER WELL RECORD Form WWC-5 Division of Water Resources App. No.								
provide a second s			Fraction		Section Number		Range Number	
	nty: Rei		NW 1/4 NW 1/4 SW	14 SW 14		T 23 S	R5 □E ØW	
Stre	Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:			
1		town or intersection: If at o		Latitude: $1.1.10.09.09.5.5.5.5.5.5.5.5.5.5.5.5.5.5.5.5.$				
	1/4 mi. north of Mayfield Road and US Hwy 50 on east side of					Longitude:150.J.Z.8.Z		
Mayfield					Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: VIGindustries					Collection Method:			
	RR#, Street Address, Box #: 3033 Campus Drive City, State, ZIP Code : Plymouth MN 55441					GPS unit (Make/Model:) Digital Map/Photo, Topographic Map, Land Survey		
City, State, ZIP Code : Plymouth, MN 55441					Est. Accuracy: $\bigcirc <3 \text{ m}, \bigcirc 3-5 \text{ m}, \bigcirc 5-15 \text{ m}, \bigcirc >15 \text{ m}$			
3 LOCATE WELL								
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .95.0 ft.							
SEC	N Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL. 11.58							
	Pump test data: Well water wasft. after hours pumping							
EST. YIELD								
w	W E Bore Hole Diameter 125 in. to 95.0 ft., and in. to in. to in. to in. to							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
X SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) X Inrigation Industrial Domestic-lawn & garden Monitoring well Industrial								
X Image: Sector of the sec								
s If yes, mo/day/yr sample was submitted								
	1 mile		fected? 🗌 Yes 🛛 🕅					
5 TYPE OF CASING USED: Steel 🗹 PVC 🗌 Other								
CASING JOINTS: Glued Clamped Welded D Threaded								
Casing diameter .1 in. to .90.0 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface. 0 in., Weight								
				••••••	lbs./ft., Wall this	kness or gauge No	5. <u>\$CN 40</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel V Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
SCREEN-PERFORATED INTERVALS: From								
From ft. to ft., From ft., brom								
GRAVEL PACK INTERVALS: From								
From								
Grout Intervals: From .0								
What is the nearest source of possible contamination:								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well								
		m well						
FROM	TO	LITHOLOG		FROM			GGING INTERVALS	
0	11.5	sand with silt and clay						
11.5	78.8	sand				· · · · · · · · · · · · · · · · · · ·		
78.8	79.0	clay						
79.0 94.5	94.5 95.0	sand shale						
94.0	33.0					<u></u>	<u> </u>	
	1							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year).								
Kansas Water Well Contractor's License No604 This Water Well Record was completed on (mo/day/year)								
under the business name of Environmental Priority Service, Inc. by (signature) VIA A M.C.								
INSTRU	CTIONS:	Use ty pewriter or ball point pen.	PLEASE PRESS FIRMLY	and <u>PRINT</u> clea	rly. Please fill in blanks	and check the correct		
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at								
http://www.kdheks.gov/waterwell/index.html.								