		L RECORD	Form WV	VC-5			r Resources App. N		
	ATION (ty: Rend	OF WATER WELL:	Fraction SE 1/4 NW 1/4 NE	1/4 SW 1/4		n Number 15	Township No. T 23 S	Range Number R 5 □E 🗷 W	
		Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:			
from i	om nearest town or intersection: If at owner's address, check here .					Latitude: 38.04932 (in decimal degrees)			
Ave.	Ave. G and Obee Rd. 1/2 N 1/2 W					Longitude: 097.85967 (in decimal degrees) Elevation: 1525			
						Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: NGL, LLC					Collection Method				
an an arm a t			outh Yale. #805	☐ GPS unit (Make/Model: Garmin 62S ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey					
City,	State, Zi	Tulsa, C	oklahoma 74136		Est. Ac	curacy: \square	<3 m, Z 3-5 m,] 5-15 m,	
3 LOCA				60					
	I AN "X"								
SECI	ION BOX	Depth(s) Groundwater Encountered (1)							
	Pump test data: Well water wasft. after hours pumping gpm								
NW	EST. YIELDgpm. Well water was								
w	V E Bore Hole Diameter 19in. to .99ft., andin. toft.								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
SW SE Domestic Feedfot Off field water supply Dewatering Domestic Specify below) Fire well F									
Was a chemical/bacteriological sample submitted to Department? Yes V No									
S If yes, mo/day/yr sample was submitted									
1 mile Water well disinfected?									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded let d									
Casing diameter .8 in. to .40 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft., Casing height above land surface .18 in., Weight .160 lbs./ft., Wall thickness or gauge No332									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ✓ Stainless Steel ☐ PVC ☐ Other (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
GRAVEL PACK INTERVALS: From 60 ft. to 20 ft., From ft. to							to ff		
From									
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☑ Other ☐ Soil									
Grout Intervals: From .29									
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)									
	Sewer lines								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None									
FROM	tion fron	wellLITHOLOG		FROM	TO TO			UGGING INTERVALS	
0	2	Top soil	TIC FOO	PROM	10	LITHO, L	ACC (COIIL.) OI FL	OGOING INTERVALS	
2	6	Brown clay					*		
6	20	Medcourse sand/grav	/el						
20	45	Medfine sand/gravel							
45	60	Medfine sand							
						,			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, □ reconstructed, or □ plugged									
under my jurisdiction and was completed on (mo/day/year) .9/4/2013									
under the business name of Rosencrantz-Bemis Ent. by (signature)									
INSTRU	CTIONS:	Use ty pewriter or ball point per	a. <u>PLEASE PRESS FIRML</u>)	and PRINT cl	early. Plea	ase fill in blank	ks and check the corr	ect answers. Send three copies	
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.									
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at									

Check: White Copy, Blue Copy, Pink Copy