			WATE	R WELL RECORD	Form WWC-5	KSA 82a-1	212 ID No	
	ON OF WATE		Fraction			tion Number	Township Number	Range Number
County:	Re	eno	NW 1/4	SW 1/4	NE ¼	16	т <b>23</b> s	R <b>5</b> W
2 <sup>no</sup> & Kirl	by – Hutchi	nson		ress of well if locat				
				ort, V&M Tran	sport, Inc.			
	dress, Box#						Board of Agriculture,	Division of Water Resources
City, State, 2	ZIP Code	Hutchi	nson, KS 67	501			Application Number:	
3 LOCATE AN "X" IN	WELL'S LOC N SECTION B	ATON WITH OX:	4 DEPTH OF C	OMPLETED WELL	. 24	ft. ELEV	/ATION: 15	17.09 (TOC)
1			Depth(s) Ground	water Encountered	1 <b>10</b> .	<b>77</b> ft	. 2ft	. 3 ft. <u>9</u>
-	NW	NE	WELL'S STATIC	WATER LEVEL	10.75 ft.	below TOC	measured on mo/day/yr	. 3 ft. 9
	×	i	Pump	test data: Well w	vater was	f	t. afterhou	rs pumping gpm   g
∰ W		<del>-</del>	Est. Yield	gpm: Wellw	vater was	f	t. afterhou	rs pumping gpm n
Ì	į l		Bore Hole Diame	ter <b>3.5</b> in.	to2	4	ft. and	rs pumping gpm gpm in. to ft.
	sw	- SE	1 Domestic	3 Feed lot	5 Public water s 6 Oil field water	supply supply	8 Air conditioning 9 Dewatering	in. to ft. 11 Injection well 12 Other (Specify below)
<b>↓</b>			2 Irrigation	4 Industrial	7 I awn and can	den (domesti	c) 10 Monitoring well	The care (opening below)
	S		1					yes, mo/day/yr sample was
			submitted	acteriological sam			ter Well Disinfected? Yes	1
5 TYPE OF	F BLANK CAS	ING USED:		5 Wrought Iron		rete tile		lued Clamped
	ei			6 Asbestos-Cer				
2 PV		4 ABS		7 Fiberglass				readed Flush
					in	to	ft., Dia	in. to ft.
Casing heigh	ht above land	surface	0	n., weight	0.703	lhe #	π., Dia Wall thickness or gauge	No SCH. 40
			N MATERIAL:	, 11019111		PVC	10 Asbestos-ce	ement
1 Ste		3 Stainle		5 Fiberglass	8	RMP (SR)	11 Other (spec	ify)
2 Bra	SS	4 Galva	nized steel	6 Concrete tile	9	ABS	12 None used	(open hole)
SCREEN O	R PERFORAT		IGS ARE:	5 G	auzed wrapped		8 Saw cut	11 None (open hole)
	ntinuous slot		Mill slot	6 W	Vire wrapped		9 Drilled holes	
			Key punched		orch cut		10 Other (specify)	
SCREEN-PI	ERFORATED	INTERVALS:	From	14 ft. to	24	ft. F	rom	ft. toft.
			From	ft. to		ft. F	rom	ft. toft.
GR/	AVEL PACK I	NTERVALS:			24	ft. F	rom	ft. toft.
6			From	ft. to		ft. F		ft. to ft.
GROUT	MATERIAL:	1 Neat	cement 2	Cement grout	3 Ber	ntonite	4 Other	
Grout Interv	als From	2	ft. to 10	ft. From	ft.	to	ft. From	ft. toft.
What is the	nearest source	e of possible	contamination:			10 Lives	tock pens 14	Abandoned water well
	otic tank wer lines		4 Lateral lines	7 Pit p	•		•	Oil well/ Gas well
	wer iines itertight sewer	lines	<ul><li>5 Cess pool</li><li>6 Seepage pit</li></ul>	8 Sew 9 Fee	age lagoon		izer storage 16 ticide storage	Other (specify below)
Direction fro	•		5 Coopage pit	3 1 66	ayara	How many		
FROM	TO	CODE		OGIC LOG	FROM	TO		G INTERVALS
0	2		ty Clay, brown					
2	15		nd, well sorted	, brown, fine to				
2	15		dium grained	ed, brown, fine to		+		
15	24		arse grained	Je, Diowii, illie u				
							GPS: (Datum WG	884)
						+	Latitude: N 38.053	
							Longitude: W 97.8	
7 CONTRA	ACTOR'S OR	LANDOWNE	R'S CERTIFICATION	ON: This water wel	l was (1) constru	cted, (2) reco	nstructed, or (3) plugged u	under my jurisdiction and was
completed on (mo/day/yr) 08/12/14 and this record is true to the best of my knowledge and belief. Kansas								
Water Well	Contractor's L	icense No.		531			ecord was completed on (	mo/day/yr) 11/12/14
under the bi	usiness name	of	GSI Engi	neering, LLC	b	v (signature)	soun Was	(
INSTR	UCTIONS: Ple	ase fill in blank	s and circle the corr	ect answers. Send the	ree copies to Kan	sas Departmer	nt of Health and Environmen DWNER and retain one for y	t, Bureau of Water, 1000 S W
Jackso	11 01., 016. 420,	i opeka, Kansa	30 000 12-130/. 10le	priorie. 913-296-554	io. Send one to W	MIEK WELL	JVVINER and retain one for y	our records.