

1 LOCATION OF WATER WELL: County: RENO 078		Fraction SW$\frac{1}{4}$ NW$\frac{1}{4}$ NW$\frac{1}{4}$	Section 4	Township Number T 23 S	Range Number R 5 W
Distance and direction from nearest town or city street address of well if located within city? 2720 North Halstead, Hutchinson KS 67502					
2 WATER WELL OWNER: Paul M. Zeyen RR#, St. Address, Box #: 2720 N. Halstead City, State, ZIP Code: Hutchinson KS 67502			Board of Agriculture, Division of Water Resource: Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 3/10/93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XXX1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement XX 9 Other (specify below) Welded 7 Fiberglass GALVANIZED Threaded Blank casing diameter 5 in. to ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 75" below WPA , weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) N/A 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From N/A ft. to N/A ft., From ft. to ft. GRAVEL PACK INTERVALS: From N/A ft. to N/A ft., From ft. to ft.			
		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout XX 3 Bentonite 4 Other Grout Intervals: From 38 ft. to 6'3" WPA From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage XX 16 Other (specify below) HOUSE Direction from well? NORTH How many feet?			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG		<div style="text-align: center; border: 1px solid black; padding: 10px;"> RECEIVED MAR 19 1993 BUREAU OF WATER </div>	
38' 6'3" Bentonite					
6'3" 0 Basement					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was plugged plugged under my jurisdiction and was completed on (mo/day/year) 3/11/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 3/18/93 under the business name of ADVANCE TERMITE & PEST CONTROL, INC. by (signature) <i>Al Wells</i> Al Wells					
INSTRUCTIONS: Use typewriter or ball point pen, <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					