WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | S | Section number | | Township number | Range number | ange number | |
|---|--|-------------------------------|--------------------------|----------------|--------|--|---|------------------|--|
| . Location of well: | Reno | 10 NW1/4 SW1/4 NE1/4 | | 6 | | т 23 s | r 5 | E 🐼 | |
| Distance and direct | tion from nearest town or city: 2600 location if in city: | Nevada | 3. Owner of R.R. or stro | | 5 | 10 E. 17 | Realty | 2 1 | |
| | Hut | Chinson Sketch map: | City, state | , zip c | ode: H | utchinson 6. Bore hole dia. 2 in | Kan. 6 | 1501 | |
| 4. Locate with "X" in section below: N house | | | | | | Well depth 27 ft. 4-26-77 | | | |
| | | | | | | 7 Cable tool Rotary Driven Dug Hollow rod Jetted Reverse rotary | | | |
| NW X NE Sewer | | | | | | 8. Use: Domestic Public supply Industry | | | |
| w | i i | Lowell | | | | ₩ - | ir conditioning St til field water O | ock ther | |
| in basement | | | | | | 9. Casing: Material Plas Height: boy or below | | | |
| | | | | | | Threaded Welded Glue Surface in. RMP PVC Weight lbs./ft. | | | |
| 5. Type and color of material From To | | | | | | Dia. 6 in. to 27 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No | | | |
| type and cotor of | ingrert GI | | | rom | | 10. Screen: Manufacturer's | | | |
| | Sai | ndy clay | | 6 | _//_ | Type Rmp | Dia. 6" | | |
| | fil | ne grave | | // | 15 | Slot/gauze /8 ha/ Set between | Length | 7 ft. | |
| | me | dium arau | e/ | 15 | 27 | Gravel pack? MO Size ro | | ft. | |
| | | 7 | | | | 11. Static water level: | , mo | /day/yr. | |
| | | | | | | ft. below land su 12. Pumping level below lan | d surfaces: | | |
| | | | | | | /7/2ft. after | hrs. pumping <u>20</u> hrs. pumping | g.p.m. | |
| | | | | | | Estimated maximum yield | 50 | _g.p.m. | |
| | | | | | | 13. Water sample submitted: Yes X No | mo Date | ./day/yr. | |
| | | | | | | 14. Well head completion: Pitless adapter | 12 Inches above | ment | |
| | | | | | | 15. Well grouted? Yes | TECHES GLOOVE | grade | |
| | •••• | | | | | With: Neat cement | | Concrete | |
| | | | | | | 16. Nearest source of possible | e contamination: S | ever | |
| | | | | | | ft. 20 Direction Well disinfected upon comple | | X No | |
| | | | | | | 17. Pump: Manufacturer's name | → Not installed | | |
| | | | | | | Model number | HP Vo | | |
| | | | | | | Length of drop pipe Type: | | | |
| | | | | | | Submersible Jet | Turbin | ocating | |
| El+t | | and sheet if needed) | | | | Centrifugal | Other | | |
| 18. Elevation: 19. Remarks: Well located in basement | | | | | | 20. Water well contractor's This well was drilled under m | y jurisdiction and this | report | |
| pography: | - | | | | | is true to the best of my know | vledge and belief. Fer wen | 193 | |
| Hill Slope | | | | | | Business name R 3 | tutchins | ense No. | |
| Upland Valley | | | | | | Signed John De Authorized rep | wenny Date | 5 <u>-20-7</u> 7 | |
| | e and pink copies to the Departm | east of Health and Easterness | | | L | U COMOTZOU IS | Form WV | + /C=5 | |