

1 LOCATION OF WATER WELL:		Fraction		Township Number		Range Number	
County: Reno		1/4 NW 1/4 NW 1/4		6		T 23 S S R 5 W EW	
Distance and direction from nearest town or city street address of well if located within city?							
703 East 30th, Hutchinson, Ks 67501 - Vickers Gas Station on East 30th							
2 WATER WELL OWNER: Total Petroleum Inc.							
RR#, St. Address, Box #: 1019 Burlington				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: North Kansas City, Mo. 64114				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.					
		WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 8-28-86					
		Pump test data: Well water was ft. after hours pumping gpm					
		Est. Yield na gpm: Well water was ft. after hours pumping gpm					
		Bore Hole Diameter 6 in. to ft., and in. to ft.					
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)	
				7 Fiberglass		CASING JOINTS: Glued X Clamped	
Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft.							
Casing height above land surface 2 in., weight lbs./ft. Wall thickness or gauge No.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS	
						10 Asbestos-cement	
						11 Other (specify)	
						12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes	
				7 Torch cut		10 Other (specify)	
						11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 5 ft. to 25 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 5 ft. to 25 ft., From ft. to ft.							
6 GROUT MATERIAL: X Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 5 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination: NA							
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage	
						13 Insecticide storage	
						14 Abandoned water well	
						15 Oil well/Gas well	
						16 Other (specify below)	
Direction from well? How many feet?							
FROM		TO		LITHOLOGIC LOG		FROM	
0		3		Top Soil		TO	
3		12		Brown Clay			
12		25		Sand & Gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-28-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 8-18-86 under the business name of Rosencrantz-Bemis Enterprise by (signature) Mike Flawes							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							