

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		NW 1/4 NE 1/4 NW 1/4	6	T 23 S	R 5 E 10
Distance and direction from nearest town or city street address of well if located within city? 2900 Acres Rd. Hutchinson KS MC 16					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 18.5 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 18.72 ft. below land surface measured on mo/day/yr 8/12/88			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 11 in. to 30 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
6 PVC 4 ABS 7 Fiberglass Threaded X					
Blank casing diameter 4 in. to 15 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface 3 in., weight lbs./ft. Wall thickness or gauge No. 51.90					
TYPE OF SCREEN OR PERFORATION MATERIAL:		6 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 6 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 15 ft. to 30 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From 10 ft. to 25 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL:		4 Other Vol. clay			
Grout Intervals: From Surface ft. to 10 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage			
Direction from well? NW		How many feet? 400'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Black, moist, silty clay			
2	9	lt brown, moist, silty sandy CLAY			
9	14	Gray, wet, as above			
14	30	Dark brown, sat. coarse to fine SAND w/ gravel			
		Grout Variance			
		Grouted 8/18/88			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/11/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 415 This Water Well Record was completed on (mo/day/yr) 8-19-88 under the business name of Daniel Dilling by (signature) <i>Daniel Dilling</i>					