


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		NW 1/4 SE 1/4 SE 1/4	6	T 23 S	R 5 E
Distance and direction from nearest town or city street address of well if located within city? 2004 Landon Hutchinson Kan.					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #:		Application Number:			
City, State, ZIP Code:					
F. R. Tuttle 2004 Landon Hutchinson Kan 67502					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 18 ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 6-23-88 Pump test data: Well water was 19 ft. after 1 hours pumping 30 gpm Est. Yield 75 gpm: Well water was 19 ft. after 6 hours pumping 35 gpm Bore Hole Diameter 9 in. to 19 ft., and 6 in. to 35 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped X			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded X Threaded X			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)					
7 Fiberglass					
Blank casing diameter 6 in. to 25 ft., Dia 12 in. to 25 ft., Dia 025 in. to 25 ft.					
Casing height above land surface 12 in., weight 25 lbs./ft. Wall thickness or gauge No. 025					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 25 ft. to 35 ft. From 35 ft. to 35 ft.					
GRAVEL PACK INTERVALS: From 25 ft. to 35 ft. From 35 ft. to 35 ft.					
6 GROUT MATERIAL:		3 Bentonite 4 Other			
1 Neat cement 2 Cement grout					
Grout Intervals: From 3 ft. to 19 ft. From 19 ft. to 35 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? North		How many feet? 30			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0 2 brown soil					
2 7 sandy clay					
7 10 brown clay					
10 14 fine sand					
14 17 fine gravel					
17 35 medium gravel					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-23-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 6-20-89 under the business name of Price Water Well Serv. by (signature) John Davenport					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4