

1 LOCATION OF WATER WELL:		Fraction <u>NW 1/4 NW 1/4 NE 1/4</u>		Section Number <u>6</u>		Township Number <u>T 23 S</u>		Range Number <u>R 5 E</u>			
County: <u>RENO</u>											
Distance and direction from nearest town or city street address of well if located within city? <u>20' S OF BUILDING</u>											
2 WATER WELL OWNER: <u>DWIGHT THOMAS MOTORS</u>											
RR#, St. Address, Box #: <u>1215 E. 30TH ST</u>						Board of Agriculture, Division of Water Resources					
City, State, ZIP Code: <u>HUTCHINSON, KANSAS</u>						Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: <u>28.5</u> ft. ELEVATION:								
			Depth(s) Groundwater Encountered 1. <u>18</u> ft. 2. ft. 3. ft.								
			WELL'S STATIC WATER LEVEL <u>15.9</u> ft. below land surface measured on mo/day/yr <u>2/8/91</u>								
			Pump test data: Well water was ft. after hours pumping gpm								
			Est. Yield gpm: Well water was ft. after hours pumping gpm								
			Bore Hole Diameter <u>8</u> in. to <u>28.5</u> ft., and in. to ft.								
			WELL WATER TO BE USED AS:								
			5 Public water supply		8 Air conditioning		11 Injection well				
			1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering		
			2 Irrigation		4 Industrial		7 Lawn and garden only		10 <u>Monitoring well</u>		
Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> ; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes No											
5 TYPE OF BLANK CASING USED:											
1 Steel			3 RMP (SR)			5 Wrought iron			8 Concrete tile		
<u>2 PVC</u>			4 ABS			6 Asbestos-Cement			9 Other (specify below)		
			7 Fiberglass						CASING JOINTS: Glued Clamped		
									Welded		
									<u>Threaded</u>		
Blank casing diameter <u>2</u> in. to <u>20.9</u> ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface <u>0</u> in., weight lbs./ft. Wall thickness or gauge No. <u>40</u>											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel			3 Stainless steel			5 Fiberglass			8 RMP (SR)		
2 Brass			4 Galvanized steel			6 Concrete tile			9 ABS		
									10 Asbestos-cement		
									11 Other (specify)		
									12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:											
<u>1 Continuous slot</u>			3 Mill slot			5 Gauzed wrapped			8 Saw cut		
2 Louvered shutter			4 Key punched			6 Wire wrapped			9 Drilled holes		
						7 Torch cut			10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From <u>10.9</u> ft. to <u>20.9</u> ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From <u>8.9</u> ft. to <u>26.4</u> ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other <u>VOCLAY</u>											
Grout Intervals: From <u>0</u> ft. to <u>8.9</u> ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank			4 Lateral lines			7 Pit privy			10 Livestock pens		
2 Sewer lines			5 Cess pool			8 Sewage lagoon			<u>11 Fuel storage</u>		
3 Watertight sewer lines			6 Seepage pit			9 Feedyard			12 Fertilizer storage		
									13 Insecticide storage		
									14 Abandoned water well		
									15 Oil well/Gas well		
									16 Other (specify below)		
Direction from well? <u>NORTH</u> How many feet? <u>160</u>											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
<u>0</u>		<u>5.5</u>		<u>BROWN SILTY CLAY</u>		<u>0</u>		<u>6.9</u>		<u>BENTONITE SLURRY</u>	
<u>5.5</u>		<u>15.5</u>		<u>SILTY SAND, FINE</u>		<u>6.9</u>		<u>8.9</u>		<u>BENTONITE CHIPS</u>	
<u>15.5</u>		<u>28.5</u>		<u>SAND, COARSE</u>		<u>8.9</u>		<u>26.4</u>		<u>SAND PACK</u>	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2/7/91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>524</u> This Water Well Record was completed on (mo/day/yr) <u>5/15/91</u> under the business name of <u>ALLIED LABORATORIES</u> by (signature) <u>Don Buit</u>											