

[1] LOCATION OF WATER WELL: County: Reno		Fraction $\frac{SW}{4} \frac{SE}{4}$	Section Number 6	Township Number T 23 S	Range Number R 5 E W
Distance and direction from nearest town or city street address of well if located within city? 1309 E 19th in Hutchinson					
[2] WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Vivian Anderson 1309 E 19th Hutch, KS 67502				
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					
		[4] DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: .ft.			
		Depth(s) Groundwater Encountered .ft. 1. .ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 5-8-92			
		Pump test data: Well water was 22 ft. after 1/2 hours pumping 30 gpm			
		Est. Yield .gpm: Well water was .ft. after .hours pumping .gpm			
		Bore Hole Diameter 8 in. to 43 ft., and .in. to .ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial ⑦ Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
[5] TYPE OF BLANK CASING USED:	CASING JOINTS: Glued X Clamped . Welded . Threaded .				
1 Steel 3 RMP (SR) ② PVC 4 ABS	5 Wrought iron 8 Concrete tile 9 Other (specify below)				
Blank casing diameter 5 in. to 30 ft., Dia . in. to .ft., Dia . in. to .ft. Casing height above land surface 12 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 16.0					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped ⑧ Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From .ft. to .ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 43 ft., From .ft. to .ft.					
FROM .ft. TO .ft., FROM .ft. TO .ft.					
[6] GROUT MATERIAL:	1 Neat cement 2 Cement grout ③ Bentonite 4 Other				
GROUT INTERVALS: From 2 ft. to 20 ft., From .ft. to .ft., From .ft. to .ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
③ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? W How many feet? 11					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	12	Gr Clay			
12	43	Sand & Gravel			
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-8-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 447 This Water Well Record was completed on (mo/day/yr) 6-4-92 under the business name of Miller Drilling by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					