


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 6 Township Number T 23 S Range Number R 5 E/W  
 County: Reno

Distance and direction from nearest town or city street address of well if located within city?

59 meadowlark Hutchinson

2 WATER WELL OWNER: R. Hilst  
 RR#, St. Address, Box #: 59 meadowlark Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Hutchinson Kan 67502 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 1.6 ft. 2. 1.6 ft. 3. 1.6 ft.  
 WELL'S STATIC WATER LEVEL 1.6 ft. below land surface measured on mo/day/yr 9-27-91  
 Pump test data: Well water was 17 ft. after 1 hours pumping 30 gpm  
 Est. Yield 75 gpm: Well water was 17 ft. after 1 hours pumping 30 gpm  
 Bore Hole Diameter 9 in. to 20 ft., and 6 in. to 30 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  
2 PVC 4 ABS 7 Fiberglass Threaded  
 Blank casing diameter 6 in. to 20 ft., Dia. 6 in. to 20 ft., Dia. 6 in. to 20 ft.  
 Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. 250  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 2 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft., From 20 ft. to 30 ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 30 ft., From 20 ft. to 30 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 3 ft. to 17 ft., From 17 ft. to 30 ft., From 30 ft. to 30 ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? South How many feet? 35

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Sandy soil			
2	9	Sandy clay			
9	14	fine sand			
14	17	fine gravel			
17	30	medium gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-27-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 6-15-92 under the business name of Price Water Well Serv. by (signature) John Davenport