

1 LOCATION OF WATER WELL: County: <u>Reno</u>	Fraction <u>N 1/4 NW 1/4 SE 1/4</u>	Section Number <u>6</u>	Township Number <u>T 23 S</u>	Range Number <u>R 5 EW</u>
--	--	----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1003 Lenox Ave Hutchinson.

2 WATER WELL OWNER: <u>W. E. Trezise</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>1003 Lenox Ave</u>	Application Number:
City, State, ZIP Code: <u>Hutchinson Kan 67502</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>35</u> ft. ELEVATION:
--	---

Depth(s) Groundwater Encountered 1 ft. 19 ft. 3. ft.

WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 5-20-92

Pump test data: Well water was 20 ft. after 1 hours pumping 30 gpm

Est. Yield 7.5 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 9 in. to 20 ft., and 6 in. to 35 ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes.....No X.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>6</u> in. to <u>25</u> ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>1250</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From <u>25</u> ft. to <u>35</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>3</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
Direction from well? <u>East</u>			13 Insecticide storage	16 Other (specify below)
			How many feet? <u>25</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Sandy soil			
2	12	Sandy clay			
12	16	fine sand			
16	21	fine gravel			
21	35	medium gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-20-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>193</u> This Water Well Record was completed on (mo/day/yr) <u>6-29-92</u> under the business name of <u>Price Water Well Serv.</u> by (signature) <u>John Panapant</u>
