

1 LOCATION OF WATER WELL: County: Peru Fraction: SW 1/4 SW 1/4 NW 1/4 Section Number: 6 Township Number: 23 Range Number: 5 E/W: E

Distance and direction from nearest town or city street address of well if located within city? 2500 N. Plum

2 WATER WELL OWNER: Eastwood Church RR#, St. Address, Box #: 2500 N. Plum City, State, ZIP Code: Hutchinson KS. 67502 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 8-10-92 ft.

Depth(s) Groundwater Encountered 1. 20 ft. 2. 21 ft. 3. 40 ft.

WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 8-10-92

Pump test data: Well water was 60 gpm: Well water was 21 ft. after 8 hours pumping 40 gpm

Est. Yield 60 gpm: Well water was 21 ft. after 8 hours pumping 40 gpm

Bore Hole Diameter 9 in. to 40 ft., and 40 in. to 40 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter 5 in. to 30 ft., Dia. 30 in. to 30 ft., Dia. 30 in. to 30 ft., Dia. 30 in. to 30 ft., Dia.
Casing height above land surface 14 in., weight 14 lbs./ft. Wall thickness or gauge No. SAR21

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From 30 ft. to 40 ft., From 30 ft. to 40 ft., From 30 ft. to 40 ft.

GRAVEL PACK INTERVALS: From 30 ft. to 40 ft., From 30 ft. to 40 ft., From 30 ft. to 40 ft., From 30 ft. to 40 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 40 ft., From 40 ft. to 40 ft., From 40 ft. to 40 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? South How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>12</u>	<u>Top Soil</u>			
<u>12</u>	<u>18</u>	<u>Sand & Gravel</u>			
<u>18</u>	<u>40</u>				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-10-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 440 This Water Well Record was completed on (mo/day/yr) 11-1-92 under the business name of Carl Vincent Service by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.