	Pic (มิบริเร	WATE	ER WELL RECORD	Form WV	NC-5	KSA 82a-1	1212 00	988	50	y h	nw-	- 5	
1 LOCATIO	OCATION OF WATER WELL:		Fraction				Number	Townsh	Township Number			Range Number		
County:	Ben	0	DW1/2		SE 14		7	Т 2	<u> </u>	S	R	<u> 5 </u>	EM)	
Distance a	nd direction	from nearest tov		address of well if locat										
		90	01 E11	th Street	Hut	chr	-502-	Ks						
2 WATER	R WELL OW	/NER:	Pir On	ick Inc										
	Address, Box	x # :		orth Main				Board	of Agr	iculture	, Division	of Water	Resources	
City, State	, ZIP Code	:	Hutchi	-son Ks	97501	/		Applic	ation N	lumber:				
		OCATION WITH	1 1 7 '	COMPLETED WELL.			H FIEVAT	ION:						
	IN SECTIO			dwater Encountered	1 8	' خ	ft 2	Ю		 ft	3	•	ft.	
- r	<u> </u>	` 		C WATER LEVEL . /										
†	i				-									
	- NW	NE	1	np test data: Well wa						•			_	
1	Est. Yield gpm; Well water was ft. after hours pumping													
l≝ w ⊢	W Bore Hole Diameter. d. 14. in. to										π.			
-	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well													
	_ SW	SE	1 Domestic					Dewatering			2 Other (S		•	
	1	1	2 Irrigation			-		Monitoring						
				/bacteriological sample	submitted	to Depai				-	s, mo/day/	· \.	e was sub-	
-			mitted					er Well Disin			·	No 🖊	<u>. </u>	
5 TYPE C	OF BLANK (CASING USED:		5 Wrought iron	8 C	oncrete 1	tile	CASING	JOIN"	rs: Glu	ed	. Clampe	d	
1 Ste		3 RMP (SI	R)	6 Asbestos-Cement	9 0	ther (spe	ecify below))			lded			
(2)PV	'C	4 ABS		7 Fiberglass		·	<u></u>				eaded			
Blank casii	ng diameter	?	.in. to /.0.0	ِ ft., Dia										
Casing hei	ight above la	and surface	<i>O.O</i>	<i>یک</i> in., weight	=44	<i>0</i>	lbs./ft	. Wall thickn	ess or	gauge	No	• • • • • •		
TYPE OF	SCREEN O	R PERFORATIO	N MATERIAL:		\boldsymbol{G}	PVC		10	Asbes	tos-cen	nent			
1 Ste	el	3 Stainless	s steel	5 Fiberglass	ε	B RMP (SR)	11	Other	(specify	y)			
2 Bra	2 Brass 4 Galvanized steel 6 Concrete tile						9 ABS			12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wr						ed		8 Saw cut			11 Nor	ne (open	hole)	
1 Continuous slot								9 Drilled ho	oles					
2 Lo	uvered shut	ter 4 K	ey punched	7 Toro				10 Other (sp			<u></u> .			
SCREEN-F	PERFORATI	ED INTERVALS:	From	. ft. to ft. to .	21.0) 	ft., From	 ا		ft.	to		ft.	
			From <u>.</u>	 ft. to .			ft., From			ft.	to <u></u> .		ft.	
	BRAVEL PA	CK INTERVALS:	: From	. ft. to	<i>91.</i> 9	5 <i></i> .	ft., From	سم ا		ft.	to		ft.	
			From	ft. to			ft., From		-	ft.	to		ft.	
6 GROUT	MATERIAL	.: ①Neat	cement	2 Cement grout	(3)E	3entonite	4 0	Other						
Grout Inter	rvals: Froi	m O:O	.ft. to . 🗫 - O.	ft., From 🤗	4. O	ft. to.	. ججر.	ft., Fro	m		ft. to			
What is the	e nearest so	ource of possible	contamination:				10 Livesto	ock pens		14	Abandone	d water	well	
1 Septic tank 4 Lateral lines				7 Pit privy		(T Fuel st	torage		15	Oil well/G	as well		
2 Sewer lines 5 Cess pool 8 S				8 Sewage la	goon		12 Fertiliz			16	Other (spe	ecify belo	ow)	
3 Wa	atertight sew	er lines 6 Seep	page pit	9 Feedyard	-		13 Insection	cide storage						
Direction for	=	·	•	·			How many	•						
FROM	ТО		LITHOLOGIC	LOG	FRO	М	то		PLU	GGING	INTERVA	LS		
0.0	0.6	Topsoi	1											
0.6	4.5	12 K 13~	53 b cl											
4.5	8.0	L+ Br 5						·						
4.5	85	One 130	· · · · · · · · · · · · · · · · · · ·											
8.5	17.5		msa ta	۶ س										
17.5	21.5		- C 54											
, -		,												
												markation was a non-resident		
							l							
7 CONTR	RACTOR'S (OR LANDOWNE		TON: This water well										
		/year)										and belie	et. Kansas	
				This Water							/. & .4/	• • • • • • •		
				sulta-to J.			by (signatu	ire) Mc	her	VO)	ma	gon	<u> </u>	
INSTRU	CTIONS: Use ty th and Environm	pewriter or ball point nent, Bureau of Water	pen. <u>PLEASE PRESS</u> , Topeka, Kansas 666	FIRMLY and PRINT clearly. I 20-0001. Telephone: 913-296	Please fill in bl i-5545. Send o	anks, unde one to WAT	rline or circle t ER WELL OW	the correct ansv NER and retain	ers. Sendone for y	d top thre our recor	e copies to 1 ds.	(aneas Dep	artment	