

1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 NE 1/4 Section Number 11 Township Number T 23 S Range Number R 5 E
 County: Reno

Distance and direction from nearest town or city street address of well if located within city?

1/2 mi. S. of 17th & Mayfield Rd E. of Hutchinson

2 WATER WELL OWNER: Virgil Zolman
 RR#, St. Address, Box #: RR1
 City, State, ZIP Code: Buhler Kansas
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	
E	SW	SE	
S			

4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION: 3-13-84
 Depth(s) Groundwater Encountered 1. 15 ft. 2. 15 ft. 3. 15 ft.
 WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 3-13-84
 Pump test data: Well water was 32 ft. after 1 hours pumping 15 gpm
 Est. Yield 20 gpm: Well water was 32 ft. after 1 hours pumping 15 gpm
 Bore Hole Diameter 12 in. to 70 ft., and 70 in. to 70 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded X
 Blank casing diameter 6 in. to 45 ft., Dia 45 in. to 45 ft., Dia 45 in. to 45 ft.
 Casing height above land surface 12 in., weight 12.55 lbs./ft. Wall thickness or gauge No. 12.55
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 10
 SCREEN-PERFORATED INTERVALS: From 45 ft. to 70 ft., From 45 ft. to 70 ft., From 45 ft. to 70 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 70 ft., From 13 ft. to 70 ft., From 13 ft. to 70 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 1
 Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? West How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	11	fine sand			
11	14	sandy clay			
14	19	fine sand			
19	22	clay			
22	23	fine sand			
23	34	clay			
34	68	fine sand			
68	70	clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-13-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 5-20-84 under the business name of Price Water Well Service by (signature) John Davanyant

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.