

1 LOCATION OF WATER WELL: County: Reno	Fraction <u>SE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	Section Number 12	Township Number T 23 S	Range Number R 5 E/W
---	---	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Harold Schwiethale RR#, St. Address, Box # : 3300 Garden Grove City, State, ZIP Code : Hutchinson, Kansas 67501	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 7.4 ft. ELEVATION:
--	---

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 1.4 ft. below land surface measured on mo/day/yr 2/16/94

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to 70 ft., and in. to ft.

WELL WATER TO BE USED AS:

☒ 1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
☒ 2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 28 ft., Dia 68 in. to 74 ft., Dia			Threaded
Casing height above land surface 24 in., weight			lbs./ft. Wall thickness or gauge No. 0.258
TYPE OF SCREEN OR PERFORATION MATERIAL:	☒ 7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	☒ 8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 28 ft. to 68 ft., From		
GRAVEL PACK INTERVALS:	From ft. to ft., From		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Hole plug
Grout Intervals:	From ft. to ft., From			
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3 1/2	Sandy top soil			
3 1/2	17	Sandy brown clay			
17	30	Brown clay with streaks of sand			
30	33	Light colored clay			
33	47	Brown clay with streaks of fine sand			
47	62	Brown clay			
62	66	Soft clay with fine sand			
66	74	Clay			
74		Shale red bed			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/16/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 3-10-94 under the business name of Rosencrantz-Bemis Ent. Inc. by (signature) <i>Doug Dodson</i>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.