

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>SE 1/4 NW 1/4 SW 1/4</u>	<u>12</u>	T <u>23</u> S	R <u>5</u> E
Distance and direction from nearest town or city street address of well if located within city? <u>2 mi E, 1/4 N of Hutchinson - 708 N Mayfield Rd</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>56</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>8</u> ft. below land surface measured on mo/day/yr <u>9-5-88</u>			
		Pump test data: Well water was <u>50</u> ft. after <u>2</u> hours pumping <u>25</u> gpm			
		Est. Yield <u>25</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>10</u> in. to <u>59</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering <u>12 Other (Specify below)</u>			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Pond</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u> ...; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped			
1 Steel		5 Wrought iron			
3 RMP (SR)		8 Concrete tile			
<u>2 PVC</u>		6 Asbestos-Cement			
4 ABS		9 Other (specify below)			
Blank casing diameter <u>6</u> in. to <u>26</u> ft., Dia		7 Fiberglass			
Casing height above land surface <u>12</u> in., weight		Welded			
TYPE OF SCREEN OR PERFORATION MATERIAL:		Threaded			
1 Steel		<u>7 PVC</u>			
3 Stainless steel		10 Asbestos-cement			
5 Fiberglass		11 Other (specify)			
8 RMP (SR)		12 None used (open hole)			
2 Brass		9 ABS			
4 Galvanized steel		6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped			
1 Continuous slot		<u>8 Saw cut</u>			
3 Mill slot		11 None (open hole)			
2 Louvered shutter		6 Wire wrapped			
4 Key punched		9 Drilled holes			
SCREEN-PERFORATED INTERVALS:		7 Torch cut			
From <u>26</u> ft. to <u>56</u> ft., From		10 Other (specify)			
GRAVEL PACK INTERVALS:		From			
From <u>20</u> ft. to <u>59</u> ft., From		ft. to			
From		ft. to			
6 GROUT MATERIAL:		1 Neat cement			
2 Cement grout		<u>3 Bentonite</u>			
4 Other					
Grout Intervals: From <u>2</u> ft. to <u>20</u> ft., From		ft. to			
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		14 Abandoned water well			
4 Lateral lines		11 Fuel storage			
7 Pit privy		15 Oil well/Gas well			
2 Sewer lines		12 Fertilizer storage			
5 Cess pool		<u>16 Other (specify below)</u>			
8 Sewage lagoon		<u>Pond</u>			
3 Watertight sewer lines		13 Insecticide storage			
6 Seepage pit		9 Feedyard			
Direction from well? <u>S</u>		How many feet? <u>20</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	11	F Sand			
11	16	Br Clay			
16	37	F Sand			
37	46	Br Clay			
46	56	F Sand			
56	59	Red clay			
59	-	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>1</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-5-88</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>447</u> This Water Well Record was completed on (mo/day/yr) <u>6-4-89</u> under the business name of <u>Miller Drilling</u> by (signature) <u>Egan Miller</u>					