

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Reno	Fraction SE 1/4 NE 1/4 NW 1/4	Section number 13	Township number T 23 S	Range number R 5 E
2. Distance and direction from nearest town or city: 2 1/2 M. E of				3. Owner of well: Herb Alkire		
Street address of well location if in city: Hutchinson, KS				R.R. or street: RT 4		
				City, state, zip code: Hutchinson, KS 67501		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 10 in. Completion date 4-27-76		
				Well depth 36 ft.		
5. Type and color of material		From	To	7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug		
Dune Sand		0	10	<input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
clay gray		10	12	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry		
Sandy clay yellow		12	18	<input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock		
Sand - F.		18	20	<input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Sandy clay yellow + gray		20	32	9. Casing: Material PLST Height: Above or below		
clay red		32	36	Threading: <input checked="" type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in.		
				RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 1.95 lbs./ft.		
				Dia. 6 in. to 36 ft. depth Wall Thickness: inches or		
				Dia. 6 in. to 36 ft. depth gage No. 200		
				10. Screen: Manufacturer's name Jess + Howell		
				Type RMP Dia. 6"		
				Slot/gauze 3/32" Length 20'		
				Set between 12 ft. and 32 ft.		
				Gravel pack? <input checked="" type="checkbox"/> Size range of material F-5"		
				11. Static water level: 1.5 ft. below land surface Date 4-27-76		
				12. Pumping level below land surfaces:		
				34 ft. after 1/2 hrs. pumping 7.5 g.p.m.		
				34 ft. after 1 hrs. pumping 7.5 g.p.m.		
				Estimated maximum yield 7.5 g.p.m.		
				13. Water sample submitted: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date 4-27-76		
				14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter 12 inches above grade		
				15. Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete		
				Depth: From 3 ft. to 6 ft.		
				16. Nearest source of possible contamination:		
				ft. 60 Direction W Type Sewer		
				Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: Not installed		
				Manufacturer's name Valley Steel		
				Model number 5 HP 13 Volts 230		
				Length of drop pipe 30 ft. capacity 6 g.p.m.		
				Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine		
				<input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating		
				<input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:		19. Remarks:				
Topography:						
<input type="checkbox"/> Hill						
<input checked="" type="checkbox"/> Slope						
<input type="checkbox"/> Upland						
<input type="checkbox"/> Valley						
		20. Water well contractor's certification:				
		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.				
		Miller Water Well Serv.				
		Business name Hutchinson, KS. License No.				
		Address Hutchinson, KS.				
		Signed Joe Miller Date 6-15-76				
		Authorized representative				

23
 5
 13
 SE
 NE
 NW
 1/4
 1/4
 1/4

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5