		WATER \	WELL RECORD	Form WWC-5	KSA 82	e-1212		
	N OF WATER WELL:	Fraction	_		on Numbe		umber	Range Number
	RENO	1/4		JW 1/4	15	<u> T 23</u>	s	R 5 E/W
Distance and	d direction from nearest tow	n or city street addr	ess of well if locat	ted within city?				
1								
	WELL OWNER: CITY	OF HUTCH	INSON					
•	idress, Box # : Moi	JITOR WELL	► ZA				•	Division of Water Resources
City, State, 2	ZIP Code :					Application		
LOCATE '	WELL'S LOCATION WITH SECTION BOX:	4 DEPTH OF COM	PLETED WELL	62	. ft. ELEV	ATION: 5.	G = G	.L
7N 7 II	N SECTION BOX.	Depth(s) Groundwar						
ī	!	WELL'S STATIC W	ATER LEVEL	33 ft. be	low land su	urface measured on	mo/day/yr	<i>8-</i> 29-84
	NW NE	Pump te	est data: Well wa	ter was	ft.	after	hours pu	mping gpm
[-		Est. Yield	. gpm: Well wa	ter was	ft.	after	hours pu	mping gpm
_≅ w ⊢	i * #	Bore Hole Diameter	· 6.1.z in. to	o	ft.,	and	in.	to
* w -	! ! !	WELL WATER TO	BE USED AS:	5 Public water	supply	8 Air conditioning		Injection well
ī	CW CE	1 Domestic	3 Feedlot	6 Oil field water	er supply	9 Dewatering	12	Other (Specify below)
[. 344 35	2 Irrigation	4 Industrial					
		Was a chemical bac	teriological sample	submitted to Dep	oartment? `	YesNo	; If yes,	mo/day/yr sample was sub-
	Ş	mitted 8-29	-84		W	ater Well Disinfecte	d? Yes	No
TYPE OF	BLANK CASING USED:	5	Wrought iron	8 Concret	e tile	CASING JO	NTS: Glued	I Clamped
1 Stee	a RMP (SF	₹) 6	Asbestos-Cement	t 9 Other (s	specify belo	ow)	Welde	ed
(2)PVC	4 ABS	7 7	Fiberglass					ded
Blank casing	g diameter 2	in. to 6.2	ft., Dia	in. to .		ft., Dia		in. to ft.
Casing heigh	ht above land surface	2-5.#i.m	, weight		Ibs	./ft. Wall thickness	or gauge Ne	SCHED. 40
TYPE OF S	CREEN OR PERFORATIO	N MATERIAL:		O PVC	;	10 Asb	estos-ceme	nt
1 Stee	d 3 Stainless	s steel 5	Fiberglass	8 RMF	P (SR)	11 Oth	er (specify)	
2 Bras	s 4 Galvaniz	ed steel 6	Concrete tile	9 ABS		12 Nor	e used (op	en hole)
SCREEN OF	R PERFORATION OPENIN	GS ARE:	5 Gau	zed wrapped		8 Saw cut		11 None (open hole)
1 Cont	tinuous slot 3 M	ill slot	6 Wire	e wrapped		9 Drilled holes		
2 Louv	vered shutter 4 Ke	ey punched	7 Toro	ch cut		10 Other (specify	')	
SCREEN-PE	ERFORATED INTERVALS:	From5	. 7 ft. to .	62	ft., Fr	om	ft. t	o
		From	ft. to .		ft., Fr	om	ft. t	o
GF	RAVEL PACK INTERVALS:	From	ft. to .	62	ft., Fr	om	ft. t	o
•		From	ft. to		ft., Fr	om	ft. t	o ft.
GROUT N	MATERIAL: 1 Neat of	cement (2)	Cement grout	3 Benton	ite 4	1 Other		
Grout Interva	als: From O	ft. to 	. ft., From	ft. to	o _. .	ft., From		ft. to
What is the	nearest source of possible	contamination:			10 Live	stock pens	14 A	bandoned water well
1 Sept	tic tank 4 Later	al lines	7 Pit privy		11 Fue	l storage	15 O	il well/Gas well
2 Sewe	er lines 5 Cess	pool	8 Sewage la	goon	12 Fert	ilizer storage	16 O	ther (specify below)
3 Wate	ertight sewer lines 6 Seep	age pit	9 Feedyard		13 Inse	ecticide storage		
Direction fro	m well?				How m	any feet?		
FROM	то	LITHOLOGIC LO		FROM	то		LITHOLOG	IC LOG
0	4 OBCLAYEYS		CLAY					
4	1602BROWN	SILTY S	SAND (-
6	3505 V. FU-N	REDIUM S	AND					
35	63 15 BROWN	COARSE S	HO F GRAVE	1				
								<u></u>
		_						
CONTRA	CTOR'S OR LANDOWNE	P'S CERTIFICATION	. This water well	was Miconstruc	ted (2) red	constructed or (3) r	duaged unc	ler my jurisdiction and was
_	n (mo/day/year)	-27-84		_				owledge and belief. Kansas
							G A.	wiguye and belief. Natisas
							10	D
INSTRUCTION	usiness name of Auso	NOINT DE DI FASE	PRESS FIRMIVA	LNUKON MBI	Dy (Sign	in blanks underli	or circle the	e correct answers. Send ton
	to Kansas Department of He							
	d retain one for your record			,			- +	
								