			WATE	ER WELL RECOR	RD Form W	WC-5 KSA 8	32a-1212		1.				
LOCATION OF WATER WELL:			Fraction	Fragtion			Section Number Towns			ship Number Range Nu			
County:	Reno	<b>)</b>	NW 1/		NE 1/4	16	T	23	S	R	5		
Distance a	340	from nearest tow		address of well if	located within	сіту'?							
_	R WELL OV		on corpo										
	Address, Bo	× # : East	on cente	/ 	A 150	•		•	-	Division of	Water	Resources	
	, ZIP Code	CATION WITH	sand, of	hio 4414	4-600	<del>*</del>		oplication I					
AN "X"	IN SECTIO	OCATION WITH N BOX:		dwater Encounter									
Mile A	   NW       SW	X   NE   E	WELL'S STATIO Pum Est. Yield Bore Hole Diam WELL WATER 1 Domestic	C WATER LEVEL op test data: We gpm: We seter.   \( \mathcal{Q}, \mathcal{Q} \). TO BE USED AS 3 Feedlot	II water was II water was In to	ft. below land ft. ft f	surface mean after after t., and 8 Air con 9 Dewate	sured on n	no/day/yi hours pi hours pi ir 11	umping umping	IO/	gpm gpm ft.	
	!	i !	2 Irrigation			and garden only	_						
Ŧ L		<u> </u>	was a cnemical mitted	/bacteriological sa	imple submitte		Yes Water Well D	•			samp	le was sub-	
5 TYPE (	OF BLANK	CASING USED:	mitted	5 Wrought iron	. 8 (	Concrete tile				ed C		ed	
1 St		3 RMP (SF	R)	6 Asbestos-Ce		Other (specify be		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		ded	•		
2 PV		4 ABS		7 Fiberglass					Thre	aded	<b>.</b>		
		4.0										ft.	
_	-	and surface		.in., weight			s./ft. Wall th			-	<b>)</b>		
	TYPE OF SCREEN OR PERFORATION MATERIAL:						PVC 10 Asbestos-cement						
				5 Fiberglass		8 RMP (SR)		11 Other (specify)					
2 Brass 4 Galvanized steel SCREEN OR PERFORATION OPENINGS ARE:					S Concrete tile 9 ABS 5 Gauzed wrapped			12 None used (open hole) 8 Saw cut 11 None (open ho					
1 Continuous slot Mill slot 6 Wire wrap							9 Drille			11 None	(open	i fiole)	
	uvered shut		ev punched	7	Torch cut								
SCREEN-	PERFORAT	ED INTERVALS:	From	<b>0.0</b> ft	. to 3	<b>D, O</b> ft., F	rom					1	
(	GRAVEL PA	CK INTERVALS:	From	B.O		<i>Q.</i> , <i>Q</i> , ft., F	From From From			to			
6 GROUT	MATERIA	L: Neat o	cemen	2 Cement grout	(3	Bentonite	4 Other					,	
Grout Inte	rvals: Fro	m	ft. to <b>B, Q</b>	ft., From .	<i></i>	. ft. to	ft.,	From		ft. to .			
What is th	e nearest s	ource of possible	contamination:				estock pens			Abandoned		well	
1 Septic tank 4 Lateral lines				7 Pit privy			11 Fuel storage 15 Oil well/Gas well						
	wer lines	5 Cess	•				ertilizer storage (6) Other (specify below)						
Direction f	atertight sev	ver lines 6 Seep South		9 Feedy	ard		secticide stor many feet?			() (( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( (	4	anks	
FROM	TO	Jean	LITHOLOGIC	LOG	FRO		narry reet?	PLU	GGING	INTERVALS			
0	19	Sandy Cla	in Light	Brown any	1								
		Light	Grenish	Brown									
_17	30	Silty Sa	nd Gre	yish Brow	vn								
			·										
							<u></u>						
				7185.74									
		grout gi	ed casino	z varianci	e								
		granted	11-22-81	B by									
		Yarryl	Plumme	r, )									
		ļ , , , , , , , , , , , , , , , , , , ,					-						
							-						
7 001	L	OD   AND CHARLES		ION. The				(5)					
7 CONTR	on (mo/do	OR LANDOWNER /year)	182	ION: This water									
			496	This \A/r			ecord is true t			nowledge ar ? - みょ.	ia dell	ei. Nansas	
water Well Contractor's License No													
INSTRU	JCTIONS: Use 1	ypewriter or ball point	pen. PLEASE PRESS			blanks, underline or ci	rcle the correct a				as Depa	artment	