

1) LOCATION OF WATER WELL: County: RENO Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 16 Township Number: 23 S Range Number: 5 EW

Distance and direction from nearest town or city street address of well if located within city?
400 S. HALSTEAD, Hutchinson, KS mu-4

2) WATER WELL OWNER: KANSAS DEPT. OF CORRECTIONS
RR#, St. Address, Box #: 900 SW JACKSON, SUITE 400N
City, State, ZIP Code: TOPEKA, KS 66612

Board of Agriculture, Division of Water Resources
Application Number: _____

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	
NW	NE
SW	SE
S	

W E

1 Mile

4) DEPTH OF COMPLETED WELL: 19.25 ft. ELEVATION: 1520.09
Depth(s) Groundwater Encountered 1. 12.5 ft. 2. - ft. 3. - ft.
WELL'S STATIC WATER LEVEL 12.47 ft. below land surface measured on mo/day/yr 3-18-93
Pump test data: Well water was - ft. after - hours pumping - gpm
Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm
Bore Hole Diameter 8 in. to 21.0 ft. and - in. to - ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 0 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes - No X; If yes, mo/day/yr sample was submitted -
Water Well Disinfected? Yes - No X

5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped -
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded -
Blank casing diameter 2 in. to 9.25 ft. Dia - in. to - ft. Dia - in. to - ft.
Casing height above land surface 5.9 in. weight - lbs./ft. Wall thickness or gauge No. 40
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) -
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) -
SCREEN-PERFORATED INTERVALS: From 19.25 ft. to 9.25 ft. From - ft. to - ft.
From - ft. to - ft. From - ft. to - ft.
GRAVEL PACK INTERVALS: From 21.0 ft. to 7.5 ft. From - ft. to - ft.
From - ft. to - ft. From - ft. to - ft.

6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other -
Grout Intervals: From 7.5 ft. to 0 ft. From - ft. to - ft. From - ft. to - ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? North Northwest How many feet? 270

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Concrete			
0.5	9.0	Grey Brown Silty Clay			
9.0	12.5	Grey Brown Sandy Silty Clay			
12.5	17.0	Grey Brown Fine Grain Sand			
17.0	21.0	Lt. Brown med-coarse Grain Sand			

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/14/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 7/22/93 under the business name of Terracon Consultants Inc by (signature) Richard Dimmick

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.