

| | | | | | |
|--|--|---|----------------|--------------------------------------|--------------|
| 1 LOCATION OF WATER WELL: | | Fraction | Section Number | Township Number | Range Number |
| County: RENO | | SW 1/4 NW 1/4 NE 1/4 | 16 | T 23 S | R 5 W |
| Distance and direction from nearest town or city street address of well if located within city? west of plant | | | | | |
| 2 WATER WELL OWNER: Eaton Corp | | Board of Agriculture, Division of Water Resources | | | |
| RR#, St. Address, Box # : 3401 E. 4th | | Application Number: | | | |
| City, State, ZIP Code : Hutchinson, KS 67501 | | | | | |
| 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: | | 4 DEPTH OF COMPLETED WELL: 44.5 ft. ELEVATION: 1520.05 | | | |
| | | Depth(s) Groundwater Encountered: 15 ft ft. 2. ft. 3. ft. | | | |
| | | WELL'S STATIC WATER LEVEL: 15 ft ft. below land surface measured on mo/day/yr | | | |
| | | Pump test data: Well water was ft. after hours pumping gpm | | | |
| | | Est. Yield gpm Well water was ft. after hours pumping gpm | | | |
| | | Bore Hole Diameter: 8 in. to 44.5 ft. and in. to ft. | | | |
| | | WELL WATER TO BE USED AS: | | | |
| | | 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well | | | |
| | | Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted | | | |
| | | Water Well Disinfected? Yes No X | | | |
| 5 TYPE OF BLANK CASING USED: | | | | | |
| 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X 7 Fiberglass Threaded X | | | | | |
| Blank casing diameter 2 in. to 34.5 ft. Dia. .69 in. to ft. Dia. in. to ft. | | | | | |
| Casing height above land surface 36 in. weight 154 lbs./ft. Wall thickness or gauge No. 154 | | | | | |
| TYPE OF SCREEN OR PERFORATION MATERIAL: | | | | | |
| 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) | | | | | |
| SCREEN OR PERFORATION OPENINGS ARE: | | | | | |
| 1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) | | | | | |
| SCREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. | | | | | |
| GRAVEL PACK INTERVALS: From 30.7 ft. to 44.5 ft. From ft. to ft. From ft. to ft. From ft. to ft. | | | | | |
| 6 GROUT MATERIAL: 1 Neat cement 9.7 2 Cement grout 9.7 3 Bentonite 30.7 4 Other | | | | | |
| Grout Intervals: From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. | | | | | |
| What is the nearest source of possible contamination: | | | | | |
| 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage | | | | | |
| Direction from well? NA How many feet? NA | | | | | |
| FROM | | TO | | LITHOLOGIC LOG | |
| FROM | | TO | | PLUGGING INTERVALS | |
| 0 | | 4 | | Clay | |
| 4 | | 5.5 | | Silt | |
| 5.5 | | 8.4 | | Clay | |
| 8.4 | | 9 | | Silt | |
| 9 | | 36 | | Sand - fine to coarse fine gravel | |
| 36 | | 56 | | Sand - v fine to coarse silty | |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/14/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 W This Water Well Record was completed on (mo/day/yr) 6/14/93 under the business name of Layne, Inc. by (signature) Steven R. Mitchell | | | | | |

