

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: RENO	SE 1/4 SE 1/4 NW 1/4	16	T 23 S	R 5 E/W

Distance and direction from nearest town or city street address of well if located within city?

311 S KIRBY - HUTCHINSON KS.

2 WATER WELL OWNER:	CITY BEVERAGE CO. - 311 S. KIRBY
RR#, St. Address, Box #	ATT: JOHN STEPHENS - P.O. BOX 685 HUTCHINSON KS 67501
City, State, ZIP Code	
Application Number:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 64 ft. ELEVATION: 12.5 ft. below land surface measured on mo/day/yr 12-22-73
	Depth(s) Groundwater Encountered 1. 11 ft. 2. — ft. 3. — ft. WELL'S STATIC WATER LEVEL 12.5 ft. below land surface measured on mo/day/yr 12-22-73 Pump test data: Well water was — ft. after — hours pumping — gpm Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm Bore Hole Diameter 7.25 in. to 64 ft. and — in. to — ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted — Water Well Disinfected? Yes — No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued — Clamped —
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	8 Welded —
Blank casing diameter 2 in. to 13 ft. Dia 2 in. to 53 ft. Dia — in. to — ft.			Threaded X
Casing height above land surface 29 in. weight SLH 40 lbs./ft. Wall thickness or gauge No. —			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) —
SCREEN-PERFORATED INTERVALS: From 13 ft. to 23 ft. From 53 ft. to 63 ft.			
SAND GRAVEL PACK INTERVALS: From 10 ft. to 64 ft. From — ft. to — ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other —
Grout Intervals: From GL ft. to 7 ft. From 7 ft. to 10 ft. From — ft. to — ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? E				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				SURFACE - WATER CAN.
				How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
64	1.5	SOIL - CLAY SILT			UPSTREAM OF WATER FLOW (NW-SE) TCE AND OTHER CHEMS - ARE IN THE GROUND WATER
1.5	4	SANDY CLAY			
4	11	SILTY SAND - FN GRAIN			
11	62.5	SAND - MED TO COARSE - CLEAN			
62.5	64	SHALE - BLUE GREY			
TD	64				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-22-93 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 12-27-93
under the business name of EBBERTS DRILLING by (signature) <i>Arnon Ebberts</i>