

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: RENO	SE 1/4 SE 1/4 NW 1/4	16	T 23 S	R 5 E

Distance and direction from nearest town or city street address of well if located within city?

311 S KIRBY - HUTCHINSON KS.

2 WATER WELL OWNER: CITY BEVERAGE CO	311 S KIRBY
RR#, St. Address, Box # ATT. JOHN STEPHENS - PO BOX 685 - HUTCHINSON KS 67509	Department of Agriculture, Division of Water Resources
City, State, ZIP Code	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: 13 ft.
	Depth(s) Groundwater Encountered 1 ft. 2. 13 ft. 3. 14.54 ft.
	WELL'S STATIC WATER LEVEL 14.54 ft. below land surface measured on mo/day/yr 12-22-93
	Pump test data: Well water was 7.25 in. to 66 ft. after 1 hours pumping 12-22-93 gpm
	Est. Yield 1 gpm: Well water was 7.25 in. to 66 ft. after 1 hours pumping 12-22-93 gpm
Bore Hole Diameter 7.25 in. to 66 ft. and 1 in. to 66 ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u>	
Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X	
2 <u>PVC</u> 4 ABS 7 Fiberglass Threaded X	
Blank casing diameter 2 in. to 15 ft. Dia 25 in. to 55 ft. Dia 1 in. to 1 ft.	
Casing height above land surface 24 in. weight SCH 40 lbs./ft. Wall thickness or gauge No. 1	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 <u>PVC</u> 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 1	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 <u>Mill slot</u> 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 1	
SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft. From 55 ft. to 65 ft.	
From 1 ft. to 1 ft. From 1 ft. to 1 ft.	
SAVD GRAVEL PACK INTERVALS: From 12.5 ft. to 66 ft. From 1 ft. to 1 ft.	
From 1 ft. to 1 ft. From 1 ft. to 1 ft.	

6 GROUT MATERIAL:	1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other 1
Grout Intervals: From 66 ft. to 10 ft. From 10 ft. to 12.5 ft. From 1 ft. to 1 ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) SURFACE-WATER CAN.	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? N	How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
66	3.5	SOIL			UP STREAM IF WATER FLOW (NW TO SE) TRICHLORETHENE AND OTHER AG. CHEMS. ARE IN GROUND WATER.
3.5	9.2	SANDY CLAY			
9.2	65.3	GRADES FROM SILTY SAND AT TOP - MED - MED COARSE TO COARSE AT BOTTOM			
65.3	66	SHALE - RED			
TD	66				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-22-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 12-27-93 under the business name of EBBERTS DRILLING by (signature) Gregory Eberts
--