

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: RENO		SE 1/4 SE 1/4 NW 1/4	16	T 23 S	R 5 E
Distance and direction from nearest town or city street address of well if located within city? EAST OF KIRBY ST AND EAST OF 300 BLOCKS KIRBY					
2 WATER WELL OWNER:		T.E.C.H. - 300 E AVE B 67509			
RR#, St. Address, Box #		ATT: MAURICE F. CUMMINGS - HUTCHINSON KS		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 59 ft. ELEVATION: —			
		Depth(s) Groundwater Encountered 1. 10 ft. 2. — ft. 3. — ft.			
		WELL'S STATIC WATER LEVEL 12.93 ft. below land surface measured on mo/day/yr 12-22-93			
		Pump test data: Well water was — ft. after — hours pumping — gpm			
		Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm			
		Bore Hole Diameter 7.25 in. to 59 ft., and — in. to — ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted —			
		Water Well Disinfected? Yes — No X			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued — Clamped — 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded — Blank casing diameter 2 in. to 9 ft., Dia 2 in. to — ft., Dia — in. to — ft. Casing height above land surface 24 in., weight SC4 40 lbs./ft. Wall thickness or gauge No. —					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) — SCREEN OR PERFORATION OPENINGS ARE: 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 9 ft. to 19 ft., From 49 ft. to 59 ft. From — ft. to — ft., From — ft. to — ft. SAND PACK INTERVALS: From 8 ft. to 59 ft., From — ft. to — ft. From — ft. to — ft., From — ft. to — ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other — Grout Intervals: From 64 ft. to 6 ft., From 6 ft. to 8 ft., From — ft. to — ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) SURFACE - WATER CAN. 13 Insecticide storage					
Direction from well? N How many feet? 250					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
64	1.5	SOIL			UPSTREAM OF WATER FLOW (NW-SE) TCE AND OTHER A.G. CHEM ARE IN GROUND WATER
1.5	7.5	SANDY SILT			
7.5	58.5	GRADES FROM SILTY SAND TO COARSE SAND WITH GRAVEL			
58.5	59	SHALE - BLUE GREY			
79	59				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-22-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 12-27-93 under the business name of EBBERTS DRILLING by (signature) <i>Robert Ebberts</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					