

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: RENO	NE 1/4 NE 1/4 NE 1/4	30	T 23 S	R 5 E/W

Distance and direction from nearest town or city street address of well if located within city?

2001 S. LORRAINE, HUTCHINSON, KS

2 WATER WELL OWNER: BIG M TRUCK STOP	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 2001 S. LORRAINE	Application Number:
City, State, ZIP Code: HUTCHINSON, KS 67501	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 13.2 ft. ELEVATION: @ 1516
	Depth(s) Groundwater Encountered 1. 10.0 ft. 2. 10.0 ft. 3. 10.0 ft. WELL'S STATIC WATER LEVEL 4.6 ft. below land surface measured on mo/day/yr 8/27/93 Pump test data: Well water was — ft. after — hours pumping — gpm Est. Yield — gpm; Well water was — ft. after — hours pumping — gpm Bore Hole Diameter 8" in. to 15.5 ft. and — in. to — ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well mw-5 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes — No ✓ ; If yes, mo/day/yr sample was submitted — Water Well Disinfected? Yes — No ✓

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued — Clamped —
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 2 in. to 3.2 ft. Dia — in. to — ft. Dia — in. to — ft.			11 Other (specify)
Casing height above land surface FLUSH in. weight — lbs./ft. Wall thickness or gauge No. 40			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 Other (specify)
1 Steel	3 Stainless steel	9 ABS	12 None used (open hole)
2 Brass	4 Galvanized steel	6 Concrete tile	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 13.2 ft. to 3.2 ft. From — ft. to — ft.			
GRAVEL PACK INTERVALS: From 15.5 ft. to 1.5 ft. From — ft. to — ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 1.5 ft. to surface ft. From — ft. to — ft. From — ft. to — ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?			How many feet? 110	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.0	ASPHALT			
1.0	4.0	DARK GREY SANDY SILTY CLAY			
4.0	7.5	Grey LT BROWN FINE-MED. GRAIN SAND			
7.5	15.5	Grey H. BROWN MED-COARSE GRAIN SAND			

RECEIVED**OCT 12 1993****BUREAU OF WATER**

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/25/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. — This Water Well Record was completed on (mo/day/yr) 8/25/93 under the business name of HUNZIKER DRILLING by (signature) David Hunziker
--