


1 LOCATION OF WATER WELL: County: RENO	Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 30	Township Number T 23 S	Range Number R 5 E (W)
--	---	-----------------------------	----------------------------------	----------------------------------

Distance and direction from nearest town or city street address of well if located within city?

2001 S. LORMINE, HUTCHINSON, KS

2 WATER WELL OWNER: BIG M TRUCK STOP RR#, St. Address, Box # : 2001 S. LORMINE City, State, ZIP Code : HUTCHINSON, KS 67501	Board of Agriculture, Division of Water Resources Application Number: 01516
--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 13.0 ft. ELEVATION: 01516 Depth(s) Groundwater Encountered 1. 10.0 ft. 2. 10.0 ft. 3. 10.0 ft. WELL'S STATIC WATER LEVEL 5.2 ft. below land surface measured on mo/day/yr 8/27/93 Pump test data: Well water was 15.5 ft. after 1 hours pumping 1 gpm Est. Yield 8 gpm Well water was 15.5 ft. after 1 hours pumping 1 gpm Bore Hole Diameter 8 in. to 15.5 ft. and 1 in. to 1 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well mw-3 Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted 1 Water Well Disinfected? Yes No
---	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter 2 in. to 2 ft. Dia 2 in. to 2 ft. Dia 2 in. to 2 ft. Casing height above land surface FLUSH in. weight 40 lbs./ft. Wall thickness or gauge No. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 13.0 ft. to 3.0 ft. From 3.0 ft. to 3.0 ft. GRAVEL PACK INTERVALS: From 15.5 ft. to 2.0 ft. From 2.0 ft. to 2.0 ft.	CASING JOINTS: Glued Clamped Welded Threaded ✓ 12 None used (open hole)
---	---

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 2.0 ft. to SURFACE ft. From 2.0 ft. to 2.0 ft. From 2.0 ft. to 2.0 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? 50' How many feet? 50'
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.0	GRAVEL			
1.0	2.5	DARK GREY SANDY SILTY CLAY			
2.5	7.0	Grey Lt-Brown FINE-MED. GRAIN SAND			
7.0	15.5	Grey Lt. BROWN MED-COARSE GRAIN SAND			

RECEIVED

OCT 12 1993

BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/25/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 10-4-93 This Water Well Record was completed on (mo/day/yr) 10-4-93 under the business name of HUNZIKER DRILLING by (signature) David Hunziker
--