

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>	<u>SW 1/4 NE 1/4 NE 1/4</u>	<u>30</u>	<u>T 23 S</u>	<u>R 5 E</u> (W)

Distance and direction from nearest town or city street address of well if located within city?

2306 S. Hwy 50 Hutchinson Kan 675022 WATER WELL OWNER: West Star Truck Service CenterRR#, St. Address, Box #: 2306 S. Hwy 50

Board of Agriculture, Division of Water Resources

City, State, ZIP Code: Hutchinson Kan. 67501

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N							
W	<table border="1"> <tr> <td>NW</td> <td>NE</td> </tr> <tr> <td>SW</td> <td>SE</td> </tr> </table>	NW	NE	SW	SE	E	
NW	NE						
SW	SE						
S							

4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION:Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 11-21-91Pump test data: Well water was 14 ft. after 1 hours pumping 30 gpmEst. Yield 75 gpm Well water was ft. after hours pumping gpmBore Hole Diameter 9 in. to 13 ft. and 6 in. to 35 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued X Clamped

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

② PVC

4 ABS

7 Fiberglass

Threaded

Blank casing diameter 6 in. to 25 ft. Dia. in. to ft. Dia. in. to ft.Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

⑦ PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

③ Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 25 ft. to 35 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:

① Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout intervals: From 3 ft. to 13 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

① Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well? EastHow many feet? 120

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Sandy soil			
3	7	Sandy clay			
7	11	Fine sand			
11	14	Fine gravel			
14	35	medium gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-21-91 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 193 This Water Well Record was completed on (mo/day/yr) 11-21-91under the business name of Price Water Well by (signature) John Davenport