			R WELL RECOR					
1 LOCATION OF V		Fraction			tion Number	1	ip Number	Range Number
County: Re	no		5W 1/4	Sw 14	31	T	2 <i>3</i> s	R 5 E/10
Distance and direc	tion from nearest to	-		•			_	l
	1 mi	5,2 E	of 50	Hutchias	on -	1420	E Mo	rgan
2 WATER WELL	OWNER: To	m Eigst	z'					
RR#, St. Address,	Box # : 142	20 E MO	gan			Board	of Agriculture,	Division of Water Resources
City, State, ZIP Co	de : Hu	Ach, KS 6	Application Number:					
	S LOCATION WITH			41	# FLEV			
AN "X" IN SEC	TION BOX:			d 1		2	ft	3
÷ 🗀	<del>-                                    </del>							7-4-93
†   i	1 1							
NW -	NE							umping <b>3.0</b> gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm  Bore Hole Diameter								
* w   1	E							n. toft.
≦ "		WELL WATER	TO BE USED AS:			8 Air condition	J	Injection well
Ī		1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering	g 12	Other (Specify below)
		2 Irrigation	4 Industria	-				
l x i		Was a chemical	bacteriological sar	nple submitted to De	epartment? \	YesNo	<b>;</b> If yes	s, mo/day/yr sample was sub-
I	\$	mitted			W	ater Well Disin	fected? Yes	X No
5 TYPE OF BLAN	IK CASING USED:		5 Wrought iron	8 Concre	ete tile	CASING	JOINTS: Glue	ed . X Clamped
1 Steel	3 RMP (S	SR)	6 Asbestos-Cer	nent 9 Other	(specify belo	ow)	Wel	ded
<b>P</b> VC	4 ABS	•	7 Fiberglass		` '	· ,	Thre	eaded
		in to 3/		in to		ft Dia		
Blank casing diameter 5. in. to 31. ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 1.2 in., weight 4.37. lbs./ft. Wall thickness or gauge No. 160.								
	N OR PERFORATION		.iii., weight	<b>7)</b> PV			Asbestos-cem	1
1 Steel	3 Stainles		5 Fiberglass	_	IP (SR)			()
2 Brass	4 Galvani		-					·
			6 Concrete tile	9 AB	3	$\overline{}$	None used (o	
	FORATION OPENI			Gauzed wrapped		8 Saw cut		11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped						9 Drilled ho		
2 Louvered s		Key punched	21	Torch cut		10 Other (sp	pecify)	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
From								
GRAVEL PACK INTERVALS: From								
		From		to 43	ft., Fr	om	ft.	to ft.
6 GROUT MATER		cement	2 Cement grout	<b>⊘</b> Bento				
Grout Intervals: From								
_	st source of possible	e contamination:			10 Live	stock pens	14	Abandoned water well
Septic tank 4 Lateral lines			7 Pit privy		11 Fuel storage		15 (	Oil well/Gas well
2 Sewer line	s 5 Ces	s pool	8 Sewag	e lagoon	12 Fertilizer storage		16 (	Other (specify below)
3 Watertight	sewer lines 6 See	9 Feedya	ard	13 Inse	ecticide storage			
Direction from wel	1? SW				How m	any feet?	25	
FROM TO		LITHOLOGIC	LOG	FROM	ТО		PLUGGING	INTERVALS
0 6	Gr Cla	V						
6 14	F Sant	y silt						
14 19	Rr +G	clau						
19 43	Br + Gr Sanl +	GANGI					W 17 2.000.0	
, , , , ,	Janzi	STA DE /					·	
							<u> </u>	***
			7.5					AT 1/2 A.M.
								<u> </u>
		-						
							· '	,
7 CONTRACTOR	S OR LANDOWNE	ER'S CERTIFICAT	ION: This water v	vell was (C)constru	cted. (2) red	constructed, or	(3) plugged ur	nder my jurisdiction and was
completed on (mo	day/year)	7-4-93			and this rec	cord is true to the	ne best of my k	nowledge and belief. Kansas
	ctor's License No.	1111	This Wa	ater Well Record wa	is completed	d on (mo/day/y	7-11	1-93
under the business		Miller 1			by (sign		mile	_
				arly Plages fill in blank-				e copies to Kansas Department
INSTRUCTIONS: C	rec typewriter or ball poin	IL POIL FLENDE PRESS	, ,, ,,,,, clei	urry. ricase IIII III DianKS,	unidefille of Cife	CIE LITE COLLECT AUSA	vers, sena top inre	c copies to natisas department