•			WA <sup>-</sup>	TER WELL RECOR	D Form W	WC-5 KSA 8	2a-1212				
		TER WELL:	Fraction NW	SW	NE	Section Namb	ı	nship Num	ber		Number
County:	Reno	678		1/4 1/4			<u> </u>	232	<u>s</u>	R 5	W <sub>E/W</sub>
Distance a	and direction 109 Clay		•	address of well if I	ocated within	city?				·	
2 WATE	R WELL OW	MEN.	idgeman Oil, Co	D.						81	
RR#, St.	Address, Bo	X #F :	Clay	(SP01			Во	ard of Agr	iculture, (	Division of Wa	ter Resources
City, State	, ZIP Code	<u>:</u> Hu	tchinson, Kans	as 6/501	25		Ap	plication N	lumber:		
LOCAT	E WELL'S L	OCATION WITH	4 DEPTH OF	COMPLETED WE	LL23	ft. ELE	VATION:	1521	8,2		a April
- AN "X"	IN SECTIO	N BOX:	Depth(s) Grou	ndwater Encountere	d 1		t. 2		ft. 3		
ı ſ		1	WELL'S STAT	IC WATER LEVEL	18.0	. ft. below land	surface meas	ured on m	no/day/yr	1/12	/95
	1			mp test data: Wel							map
-	NW	- NE	Est. Yield	gpm: Wei	water was	ft.	after		hours pu	mping	gpm
.			Bore Hole Dia	meter	n. to	. 25 	., and		in.	to	ft.
W -	1	i E	l .	TO BE USED AS:		water supply				Injection well	
-	I.	1	1 Domest	ic 3 Feedlot		ld water supply	9 Dewate	ring	12	Other (Specif	y below)
	SW	SE	2 Irrigation	n 4 Industria	l 7 Lawn	and garden only	10 Monitor				
			Was a chemica	al/bacteriological sar							
i L			mitted		•		Vater Well Di			No	X
5 TYPE	OF BLANK C	CASING USED:		5 Wrought iron	8 (	Concrete tile	CASI	NG JOIN	rs: Glued	I Clar	mped
1_St		3 RMP (S	SR)	6 Asbestos-Cer	ment 9 (	Other (specify be	low)		Welde	ed	
	مجار	4 ABS	•	7 Fiberglass					Threa	dedX.	
Blank casi	ing diameter	2	.in. to	15 ft., Dia		in. to	ft., Dia	<b>.</b>		in. to	ft.
				in., weight		ا الخ					
•	•	R PERFORATIO		,	(	PVC		10 Asbes			
1 St	eel	3 Stainles	s steel	5 Fiberglass		8 RMP (SR)		11 Other	(specify)		
2 Br	ass	4 Galvani	zed steel	6 Concrete tile		9 ABS		12 None	used (op	en hole)	
SCREEN	OR PERFOR	RATION OPENIN	NGS_ARE:	- 5	Gauzed wrap	oed	8 Saw o	eut		11 None (o	pen hole)
1 Cc	ontinuous slo	ւ Ֆ	Aill slot	6	Wire wrapped		9 Drilled	holes			
-	uvered shutt	•	(ey punched	7	Torch cut		10 Other	(specify)		<b></b>	
SCREEN-	PERFORATE	ED INTERVALS:	From		to	£5	rom		ft. to	<b>5</b>	
				ft.							
(	GRAVEL PA	CK INTERVALS				25ft., F					
			From	_	to		rom		ft. to		ft.
6 GROUT	T MATERIAL	1 Neat	cement	2 ement grout	- G	Bentonite	4 Other				
Grout Inte	rvals: Fron	n 0	.ft. to	- / /	11	. ft. to	ft., ) f	rom		ft. to	
What is th	ne nearest so	urce of possible	contamination			10 Liv	estock pens		14 A	bandoned wa	ter well
	eptic tank		rai lines	7 Pit priv	y	11 Fu	el storage		15-0	il well/Gas we	ell
	wer lines	5 Cess	s pool				illizer storage (Specify below)				
3 Watertight sewer lines 6 Seepage pit			page pit	pit 9 Feedyard			13 Insecticide storage				
	from well?	W		•		How r	nany feet?	( 12	5 /		
FROM	ТО		LITHOLOGI	C LOG	FRO	OM TO		PLU	SGING II	NTERVALS	
0	2	Clay, Dar	k Brown				MW10				
	5.5	_	ht Brown				GeoCore			lush-mount (	
5.5	10	• • •	y Light Brown				KDHE#	0207819	2	Tag # 68	099
10	1 1	•	low-Brown								
13	1 .		llow-Brown								
18	1 1	Gravel,									
21	1 1	Sand, Me	dium Yellow-B	rown							
7 CONTE	RACTOR'S	OR LANDOWNE	R'S CERTIFICA	TION: This water v	vell was	enstructed, (2) re	constructed,	or (3) plu	gged und	er my jurisdio	ction and was
completed	on (mo/dav/	year)		1/24/95							belief. Kansas
141-1 141-1	I Contractor	s License No	527						-	4/13/93	
water wel	Contractor	S License No		Core Services, Inc	iter Well Reco	rd was complete	d on (mo/day	//yr) <u>~</u>	וגי נעייי		