

1 LOCATION OF WATER WELL:		Fraction NW <input checked="" type="checkbox"/> SW <input checked="" type="checkbox"/> NE <input checked="" type="checkbox"/>		Section Number 18	Township Number 23 S	Range Number 5 W
County: Reno 078						
Distance and direction from nearest town or city street address of well if located within city? 109 Clay						
2 WATER WELL OWNER:		Bridgeman Oil, Co.				
RR#, St. Address, Box # :		109 Clay				
City, State, ZIP Code :		Hutchinson, Kansas 67501				
		Board of Agriculture, Division of Water Resources Application Number 15275				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 1527.5				
		Depth(s) Groundwater Encountered 1. 18.2 ft. 2. ft. 3. 1/12/95 ft.				
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was 25 ft. after hours pumping gpm				
		Bore Hole Diameter .in. to .ft., and .in. to .ft.				
		WELL WATER TO BE USED AS:				
		5 Public water supply 8 Air conditioning 11 Injection well				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well X				
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued . . . . . Clamped . . . . .				
1 Steel		5 Wrought iron				
2 PVC		6 Asbestos-Cement				
3 RMP (SR)		8 Concrete tile				
4 ABS		9 Other (specify below)				
5 Fiberglass		Welded . . . . . X				
Blank casing diameter 2 in. to 15 ft., Dia		Threaded . . . . .				
Casing height above land surface -1.2 in., weight		Sch. 40				
TYPE OF SCREEN OR PERFORATION MATERIAL:		3 PVC				
1 Steel		10 Asbestos-cement				
2 Brass		11 Other (specify)				
3 Stainless steel		12 None used (open hole)				
4 Galvanized steel						
5 Fiberglass		8 RMP (SR)				
6 Concrete tile		9 ABS				
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)				
1 Continuous slot		9 Drilled holes				
2 Louvered shutter		10 Other (specify)				
3 Mill slot						
4 Key punched						
SCREEN-PERFORATED INTERVALS:		From 15 ft. to 25 ft., From ft. to ft.				
		From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS:		From 13 ft. to 25 ft., From ft. to ft.				
		From ft. to ft., From ft. to ft.				
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other				
Grout Intervals: From 0 ft. to 11 ft., From 11 ft. to 13 ft., From ft. to ft.						
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) UST						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well? E		How many feet? 163				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	4	Clay, Dark Brown			MW2	
4	9	Clay, Light Brown			GeoCore # 97 Flush-mount Cover	
9	13	Sand, Light Brown			KDHE # 02078192 Tag # 109822	
13	25	Sand, Light Brown				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/24/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2/13/95 under the business name of GeoCore Services, Inc. by (signature) Dale R. R.						