


1 LOCATION OF WATER WELL: County: <u>LeNO</u>		Fraction <u>NE 1/4 NE 1/4 SW 1/4</u>		Section Number <u>9</u>		Township Number <u>T 23 S</u>		Range Number <u>R 5 E/W</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>3011 E 11th St. - 17' S of 11th & 27' E of driveway</u>									
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		<u>City of Hutchinson</u> <u>PO Box 1567</u> <u>Hutchinson KS 67504-1567</u>				Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL... <u>15.7</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>11.67</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>12.12</u> ft. below land surface measured on mo/day/yr <u>10-28-94</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>3</u> in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Piezometer</u> Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>							
5 TYPE OF BLANK CASING USED: <u>1 Steel</u> 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>1.75</u> in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>3.6 ft</u> in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel <u>3 Stainless steel</u> 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot <u>5 Gauzed wrapped</u> 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From <u>12.7</u> ft. to <u>15.7</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>2</u> ft. to <u>0</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS <u>0.0 5.0 Silty Clay</u> <u>5.0 15.7 Sand</u>									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) <u>reconstructed</u> , or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-29-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>531</u> This Water Well Record was completed on (mo/day/yr) <u>4-3-95</u> under the business name of <u>GST</u> by (signature) <u>William M. Jurn</u>									