

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>	<u>SW 1/4 SW 1/4 NE 1/4</u>	<u>30</u>	T <u>23</u> S	R <u>5</u> E <u>10</u>

Distance and direction from nearest town or city street address of well if located within city?

2212 US Hwy 50 Hutchinson KS.

2 WATER WELL OWNER: <u>Jayhawk Corp</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>PO Box 8216</u>	Application Number:
City, State, ZIP Code: <u>Waco, TX 76714</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION: <u>Bolt: 1517.06 T.Q.C. 1518.73</u>
	Depth(s) Groundwater Encountered 1. <u>11.93</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>11.93</u> ft. below land surface measured on mo/day/yr <u>3/9/95</u>
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield <u>4</u> gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: <u>7.6</u> in. to <u>20</u> ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>✓</u> If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes <u>No</u>	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2</u> PVC	4 ABS	7 Fiberglass	Welded <u>Threaded</u>
Blank casing diameter <u>10'</u> in. to <u>10'</u> ft., Dia			
Casing height above land surface: <u>30"</u> in., weight			lbs./ft. Wall thickness or gauge No. <u>Schedule 40</u>
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	<u>3</u> Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From <u>20'</u> ft. to <u>10'</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>20'</u> ft. to <u>6'</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	<u>2</u> Cement grout	<u>3</u> Bentonite	4 Other
Grout Intervals: From <u>6'</u> ft. to <u>2'</u> ft., From <u>2'</u> ft. to <u>0'</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? How many feet?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0'</u>	<u>4'</u>	<u>Sandy Clay Dark Gray</u>			
<u>4'</u>	<u>10'</u>	<u>H Brn fine to Med Grained</u>			
<u>10'</u>	<u>20'</u>	<u>Sand H Brn Med to larg grained moderately to poorly sorted</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>1</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3/8/95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>568A</u> This Water Well Record was completed on (mo/day/yr) <u>3-8-95</u> under the business name of <u>Max's Enterprises</u> by (signature) <u>David H. Hume</u>
--