

2011057 MW-8

WATER WELL RECORD


Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL: County: RENO	Fraction: NW 1/4 NW 1/4 NE 1/4	Section Number: 1	Township Number: T 23 S	Range Number: R 6 E
--	---------------------------------------	--------------------------	--------------------------------	----------------------------

Distance and direction from nearest town or city street address of well if located within city?
25 E. 30th St., HUTCHINSON, KS

2 WATER WELL OWNER: MARK COBERLY RR#, St. Address, Box #: 3217 E. MEADOWLAKE City, State, ZIP Code: HUTCHINSON, KS 67502	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 22.0 ft. ELEVATION: 1540.28 Depth(s) Groundwater Encountered 1. 16.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 1439 ft. below land surface measured on mo/day/yr 8-16-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X
---	--

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS Blank casing diameter 2 in. to ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface Flush in., weight 703 lbs./ft. Wall thickness or gauge No. Sch 40	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded FLUSH TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 12.0 ft. to 22.0 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 10.0 ft. to 22.0 ft., From ft. to ft. From ft. to ft., From ft. to ft.
--	--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 10.0 ft. to 1.5 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? IN UST BASIN How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.5	CONCRETE			
0.5	4.0	CLAY, V-SILTY			
4.0	9.0	CLAY, SILTY, SOME SAND			
9.0	16.0	SAND, FEW GRAVEL, SILTY, CLAYEY			
16.0	22.0	SAND, WITH GRAVEL			
Additional Waiver was requested on 8-17-95 by Allison Irwin					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-27-95 10-9-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10-27-95 under the business name of GSI by (signature) Steve Nudler
--