

MW-20

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: RENO		NW 1/4 SW 1/4 SW 1/4	24	T 23 S	R 6 E/W
Distance and direction from nearest town or city street address of well if located within city? 48 STATE STREET So HUTCHINSON MW-20					
2 WATER WELL OWNER: FOOD BRANDS AMERICA INC					
RR#, St. Address, Box #: 2601 NW EXPRESSWAY SUITE 1000 W					
City, State, ZIP Code: OKLAHOMA CITY, OK 73112					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 15 ft. ELEVATION: 1526.50			
<div style="text-align: center;">N ----- NW NE ----- SW SE ----- S X</div>		Depth(s) Groundwater Encountered 1. 7 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 8.24 ft. below land surface measured on mo/day/yr 9-27-95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to ft. and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter in. to ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface FIUSH in., weight .703 lbs./ft. Wall thickness or gauge No. .154					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 5 ft. to 15 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 3 ft. to 15 ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 1 ft. to 3 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)					
Direction from well? SW How many feet? 100'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	ALLUVIUM, CLAY			
4	15	POOR, WELL GRADED SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-27-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10-26-95 under the business name of GSI by (signature) Math Wolf					