

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		NE 1/4 NE 1/4 SE 1/4	14	T 23 S	R 6 EW
Distance and direction from nearest town or city street address of well if located within city?					
305 S. Monroe, Hutchinson, KS.					
2 WATER WELL OWNER:		David Weast/Krause Plow Corp.			
RR#, St. Address, Box # :		305 S. Monroe		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Hutchinson, Ks.		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 17'6" ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 11' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 11.24 ft. below land surface measured on mo/day/yr 5-22-96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 8 1/2" in. to 17'6" ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No. X..... If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. X					
Blank casing diameter 2.375 in. to ft. Dia. in. to ft. Dia. in. to SDR 13 ft.					
Casing height above land surface Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. Sch 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
SCREEN-PERFORATED INTERVALS: From 17' ft. to 7' ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 17'6" ft. to 5'6" ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 5'6" ft. to 4' ft. From 4' ft. to 0' ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage FUEL 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? EWS How many feet? 75'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Concrete			
1	2.75	Dk brn silty sand, dry to moist, earthy odor, fine grained sand.			
2.75	6	Lt brn clayey sandy silt, oxides, moist, friable, no odor.			
6	10	Fine grained sand, dry, no odor, well rounded & sorted.			
10	17'6"	Fine-very coarse grained sand & gravel, wet at 11', no odor, poorly sorted, subrounded.			
F.M. OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-18-96 and this record is true to the best of my knowledge and belief. Kansas Water Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-23-96 under the business name of JB Environmental Drilling by (signature) James Bieber					