

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Reno</u>		<u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$	<u>14</u>	T <u>23</u> S	R <u>6</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>305 S. Monroe, Hutchinson, KS.</u>					
2 WATER WELL OWNER: <u>David Weast/Krause Plow Corp.</u>					
RR#, St. Address, Box # : <u>305 S. Monroe</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Hutchinson, Ks.</u>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>17'6"</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>12'</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>12.28</u> ft. below land surface measured on mo/day/yr <u>5-22-96</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: <u>8 1/2"</u> in. to <u>17'6"</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>No</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> Blank casing diameter <u>2.375</u> in. to <u>7'</u> ft., Dia. in. to ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface <u>Flush Mt.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR 13</u> ft. <u>Sch 40</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 <u>Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>17'6"</u> ft. to <u>5'6"</u> ft., From ft. to ft., From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL:					
Grout Intervals: From <u>5'6"</u> to <u>4'</u> ft., From <u>4'</u> to <u>0'</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage <u>Fourer</u> 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>West South West</u> How many feet? <u>400'</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Concrete			
.50	4	Dk brn silty sand to sandy silt, friable, dry to moist, earthy odor.			
4	6	Med lt brn silty sand, dry to moist, no odor.			
6	9.75	Fine grained dry sand, no odor, well rounded & sorted.			
9.75	17'6"	Fine-very coarse wet sand w/ some gravel, poorly sorted, sub-rounded at 11'.			
F.M. OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-18-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>5-23-96</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James B. Brier</u>					